



TP-Link TL-MR100 wireless router Fast Ethernet Single-band (2.4 GHz) 4G Black



Model: TL-MR100

Manufacturer: TP-LINK

EAN: 1210002609258

Product Code: 1009605

R1,706

Receiver sensitivity: 11g 54M: -74dBm 11n HT20: -71dBm 11n HT40: -67dBm | Certification: CE, RoHS | Wi-Fi Multimedia (WMM)/(WME): Yes | Linux operating systems supported: Yes | Height: 36 mm | Product type: Tabletop router | Output voltage: 9 V | Harmonized System (HS) code: 85176990 | On/off switch: Yes | Width: 154 mm | Ethernet LAN: Yes | Supported network protocols: IPv4, IPv6 | Output current: 0.85 A | DHCP server: Yes | Antennas quantity: 2 | Wi-Fi standards: 802.11g | Ethernet LAN interface type: Fast Ethernet | Cabling technology: 10/100Base-T(X) | Wi-Fi standards: 802.11b | Package height: 66 mm | USB port: No | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | Wi-Fi standards: Wi-Fi 4 (802.11n) | Depth: 114 mm | IP address filtering: Yes | Browser supported: Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 | WLAN data transfer rate (max): 300 Mbit/s | Quick installation guide: Yes | Ethernet WAN: Yes | 4G bands supported: 900 | 4G bands supported: 2100 | 4G bands supported: 800 | 4G bands supported: 2300 | 4G bands supported: 1900 | 4G bands

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

supported: 2600 | 4G bands supported: 2500 MHz | 3G standards: UMTS | Wi-Fi band: Single-band (2.4 GHz) | 3G standards: HSPA | 4G bands supported: 1800 | Mobile network generation: 4G | 3G/4G USB modem compatibility: No | Firewall: Yes | Equivalent Isotropically Radiated Power (EIRP) (@IEEE 802.11n): 20 dBmW | Antenna design: External | 3G bands supported: 850 | Schedule access: Yes | WAN connection type: RJ-45 | Port triggering: Yes | Guest access: Yes | DMZ support: Yes | Port forwarding: Yes | Dynamic DNS (DDNS): Yes | SIM card type: MicroSIM | 3G bands supported: 2100 | Universal Plug and Play (UPnP): Yes | Memory card slot(s): No | SIM card slot: Yes | 4G standard: LTE-TDD & LTE-FDD | 3G bands supported: 900 MHz | WPS push button: Yes | DC-in jack: Yes | Ethernet LAN (RJ-45) ports: 2 | Operating temperature (T-T): 0 - 40 °C | Power source type: DC | Product colour: Black | DHCP client: Yes | Security algorithms: 64-bit WEP | Stateful Packet Inspection (SPI): Yes | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Security algorithms: WPA2-PSK | Reset button: Yes | Package width: 293 mm | Security algorithms: WPA | Networking standards: IEEE 802.11b | 4G: Yes | 3G: Yes | Weight: 150 g | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | AC adapter included: Yes | Ethernet LAN data rates: 100 | Antenna connector type: N-type | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Windows operating systems supported: Windows XP | Mac operating systems supported: Yes | Cables included: LAN (RJ-45) | Package weight: 480 g | Operating relative humidity (H-H): 10 - 90% | Windows operating systems supported: Windows 98SE | Wireless statistics: Yes | Windows operating systems supported: Windows 8 | Windows operating systems supported: Windows NT | Wireless radio: Yes | Package depth: 161 mm | Windows operating systems supported: Windows 7 | Security algorithms: WPA2 | MAC address filtering: Yes | Security algorithms: 128-bit WEP | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Windows operating systems supported: Windows 2000 | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950