



TP-Link 5-Port Gigabit Easy Smart PoE Switch with 4- Port PoE+



Model: TL-SG105PE

Manufacturer: TP-LINK

EAN: 1210002616850

Product Code: 1009628

R1,574

Certification: FCC, CE, RoHS | Width: 99.8 mm | Rack mounting: No | Height: 25 mm | Package height: 121 mm | Auto MDI/MDI-X: Yes | Power over Ethernet (PoE) power per port: 30 W | Power source: DC | Depth: 98 mm | Total Power over Ethernet (PoE) budget: 65 W | VLAN support: Yes | Heat dissipation: 256.3 BTU/h | Switch type: Managed | User guide: Yes | Forwarding rate: 7.44 Mpps | Switching capacity: 10 Gbit/s | Copper ethernet cabling technology: 1000BASE-T | Broadcast storm control: Yes | Link aggregation: Yes | Power over Ethernet plus (PoE+) ports quantity: 4 | Virtual LAN features: Tagged VLAN | Jumbo frames support: Yes | MAC address table: 2000 entries | Port mirroring: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Loop protection: Yes | Copper ethernet cabling technology: 100BASE-TX | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-FX | Basic switching RJ-45 Ethernet ports quantity: 5 | Number of queues: 4 | Store-and-forward: Yes | Auto-negotiation: Yes | Switch layer: L2 | Jumbo frames: 16000 | Power supply included: Yes | Harmonized System (HS)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

code: 85176990 | Cable types supported: Cat6 | Rate limiting: Yes | Cable types supported: Cat5 | Cable types supported: Cat5e | Cable types supported: Cat3 | Gigabit Ethernet (copper) ports quantity: 5 | Packet buffer memory: 1 MB | Number of VLANs: 4000 | Virtual LAN features: Port-based VLAN | Flow control support: Yes | Fanless: Yes | 10G support: No | IGMP snooping: Yes | Cable types supported: Cat4 | Input current: 1.31 A | LED indicators: Activity | Operating relative humidity (H-H): 10 - 90% | LED indicators: Link | LED indicators: Status | LED indicators: Speed | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | LED indicators: Power | Web-based management: Yes | Operating temperature (T-T): 0 - 40 °C | LED indicators: PoE | Package width: 131 mm | Power consumption (max): 75.16 W | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Product colour: Black | Networking standards: IEEE 802.3af | Storage relative humidity (H-H): 5 - 95% | Networking standards: IEEE 802.3u | Package weight: 770 g | Networking standards: IEEE 802.3i | Input voltage: 53.5 V | Package depth: 196 mm | Power over Ethernet (PoE): Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950