



TP-Link Omada 24-Port Gigabit L2+ Managed Switch with 4 SFP Slots



Model: SG3428

Manufacturer: TP-LINK

EAN: 1210002611886

Product Code: 1009629

R4,985

Operating relative humidity (H-H): 10 - 90% | Power supply included: No | Power consumption (max): 20.6 W | Jumbo frames support: Yes | Operating temperature (T-T): 0 - 45 °C | DHCP features: DHCPv6 client | SFP module slots quantity: 4 | DHCP features: DHCPv6 snooping | DHCP features: DHCP client | DHCP features: DHCP relay | 10G support: No | Storage relative humidity (H-H): 5 - 90% | Packet buffer memory: 12 MB | DHCP features: DHCP snooping | Power over Ethernet (PoE): No | Width: 440 mm | Height: 44 mm | Cables included: LAN (RJ-45) | Power source: AC | Heat dissipation: 70.3 BTU/h | Form factor: 1U | Basic switching RJ-45 Ethernet ports quantity: 24 | Depth: 180 mm | Rack mounting: Yes | DHCP features: DHCP server | Switching capacity: 56 Gbit/s | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | MAC address table: 16000 entries | IGMP snooping: Yes | VLAN support: Yes | Number of fans: 0 fan(s) | Multicast support: Yes | Number of VLANs: 4000 | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | IPv4 routes: 48 | AC input voltage: 100 - 240 V | Static port security: Yes | Broadcast storm control: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Management protocols: SNMPv1/v2c/v3, SNTP | Store-and-forward: Yes | Switch layer: L2/L3 | Virtual LAN features: Tagged VLAN | Virtual LAN features: Private VLAN | Configuring Location Settings (CLI): Yes | Virtual LAN features: Voice VLAN | Rate limiting: Yes | Ethernet LAN data rates: 10,100,1000 Mbit/s | IP-MAC-Port binding: Yes | Multicast Listener Discovery (MLD) snooping: Y | Access Control List (ACL): Yes | Head-of-line (HOL) blocking: Yes | IP routing: Yes | Link aggregation: Yes | LED indicators: Yes | AC input frequency: 50/60 Hz | Gigabit Ethernet (copper) ports quantity: 24 | Web-based management: Yes | MAC address filtering: Yes | Spanning tree protocol: Yes | Jumbo frames: 9000 | IPv4 & IPv6 features: IPv6 ping | Static route: Yes | Authentication type: AAA, RADIUS, TACACS+ | IPv4 & IPv6 features: IPv6 traceroute | Networking standards: IEEE 802.3u | MIB support: Yes | Networking standards: IEEE 802.3ab | IPv4 & IPv6 features: IPv4/IPv6 access-control list (ACL) | Networking standards: IEEE 802.3z | Virtual LAN features: Protocol-based VLAN | IPv6 routes: 48 | Quick start guide: Yes | Policy-based routing: Yes | IPv4 & IPv6 features: IPv6 Telnet | BPDU filtering/protection: Yes | ARP inspection: Yes | GARP VLAN Registration Protocol (GVRP): Yes | System event log: Yes | Forwarding rate: 41.66 Mpps | Loop protection: Yes | Networking standards: IEEE 802.3i | Number of static routes: 48 | Console port: RJ-45/Micro-USB | Cloud-managed: Yes | Product colour: Black | Flow control support: Yes | SSH/SSL support: Yes | Authentication: MAC-based authentication, Port-based authentication | Switch type: Managed | Port mirroring: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950