



TP-Link Omada 24-Port Gigabit and 4-Port 10GE SFP+ L2+ Managed Switch with 24-Port PoE+



Model: SG3428XMP

Manufacturer: TP-LINK

EAN: 1210002611619

Product Code: 1009871

R11,007

Height: 44 mm | Cables included: LAN (RJ-45) | Ethernet LAN data rates: 10,100,1000 Mbit/s | Operating relative humidity (H-H): 10 - 90% | Number of fans: 2 fan(s) | Power source: AC | Total Power over Ethernet (PoE) budget: 384 W | Quick start guide: Yes | Power consumption (max): 486.2 W | Width: 440 mm | Web-based management: Yes | Depth: 330 mm | Power over Ethernet (PoE): Yes | Rack mounting: Yes | AC input frequency: 50/60 Hz | Operating temperature (T-T): 0 - 45 °C | Networking standards: IEEE 802.1s | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.1w | Networking standards: IEEE 802.11d | Form factor: 1U | LED indicators: Yes | AC input voltage: 100 - 240 V | Product colour: Black | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Virtual LAN features: MAC address-based VLAN | Management

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

protocols: SNMPv1/v2c/v3, SNTP | Virtual LAN features: Tagged VLAN | Virtual LAN features: Private VLAN | Packet buffer memory: 12 MB | Multicast support: Yes | Virtual LAN features: Port-based VLAN | Heat dissipation: 1658.78 BTU/h | System event log: Yes | BPDU filtering/protection: Yes | DHCP features: DHCP snooping | Port mirroring: Yes | Console port: RJ-45/Micro-USB | Cloud-managed: Yes | Broadcast storm control: Yes | Spanning tree protocol: Yes | Jumbo frames: 9000 | Gigabit Ethernet (copper) ports quantity: 24 | IP-MAC-Port binding: Yes | Switch layer: L2+ | Jumbo frames support: Yes | DHCP features: DHCPv6 client | DHCP features: DHCP client | DHCP features: DHCP relay | DHCP features: DHCPv6 snooping | MAC address table: 16000 entries | Rate limiting: Yes | Link aggregation: Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | DHCP features: DHCP server | MIB support: Yes | Head-of-line (HOL) blocking: Yes | Power supply included: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | IGMP snooping: Yes | Policy-based routing: Yes | Number of static routes: 48 | VLAN support: Yes | Power connector: AC-in jack | Power over Ethernet plus (PoE+) ports quantity: 24 | Forwarding rate: 95.23 Mpps | Switching capacity: 128 Gbit/s | Switch type: Managed | Active link detection: Yes | SFP+ module slots quantity: 4 | Access Control List (ACL): Yes | Virtual LAN features: Voice VLAN | Virtual LAN features: Protocol-based VLAN | Flow control support: Yes | SSH/SSL support: Yes | 10G support: Yes | Number of VLANs: 4000 | Loop protection: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950