

TP-Link TL- SG108E network switch Managed L2 Gigabit Ethernet (10/100/1000) Black



Model: TL-SG108E

Manufacturer: TP-LINK

EAN: 1210002616928

Product Code: 1011654

R1,298

Certification: FCC, CE, RoHS | Link aggregation: Yes | Switch layer: L2 | Store-and-forward: Yes | Broadcast storm control: Yes | Jumbo frames: 16000 | Web-based management: Yes | Number of queues: 4 | Throughput: 11.9 Mpps | Auto-negotiation: Yes | Switch type: Managed | DC input voltage: 9 V | Number of multicast groups filtered: 128 | Rate limiting: Yes | Product colour: Black | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.1p | Depth: 101 mm | Jumbo frames support: Yes | AC input voltage: 100 - 240 V | Operating temperature (T-T): 0 - 40 °C | MAC address table: 4000 entries | LED indicators: Yes | Storage relative humidity (H-H): 5 - 90% | Height: 25 mm | Cables included: AC | Heat dissipation: 12.55 BTU/h | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Housing material: Metal |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Basic switching RJ-45 Ethernet ports quantity: 8 | Port mirroring: Yes | Package type: Box | Operating relative humidity (H-H): 10 - 90% | Auto MDI/MDI-X: Yes | Packet buffer memory: 1.5 MB | Switching capacity: 16 Gbit/s | Networking standards: IEEE 802.1ab | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | VLAN support: Yes | Input current: 0.6 A | Number of VLANs: 32 | Power supply included: Yes | User guide: Yes | AC input frequency: 50 - 60 Hz | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Harmonized System (HS) code: 85176990 | IGMP snooping: Yes | Power over Ethernet (PoE): No | Width: 158 mm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950