



TP-Link TL-SG108 network switch Unmanaged L2 Gigabit Ethernet (10/100/1000) Black



Model: TL-SG108

Manufacturer: TP-LINK

EAN: 1210002616898

Product Code: 1011823

R1,188

Certification: CE, FCC ,RoHS | Wall mountable: Yes | Store-and-forward: Yes | Operating relative humidity (H-H): 10 - 90% | Power supply included: Yes | Cable types supported: Cat4 | Manual: Yes | Access Control List (ACL) IPv6 entries: 11 | Copper ethernet cabling technology: 10BASE-T | Forwarding rate: 11.9 Mpps | Jumbo frames support: Yes | Jumbo frames: 16000 | Storage relative humidity (H-H): 5 - 90% | Copper ethernet cabling technology: 1000BASE-T | MAC address auto-learning supported: Yes | Switching capacity: 16 Gbit/s | Depth: 101 mm | Basic switching RJ-45 Ethernet ports quantity: 8 | Copper ethernet cabling technology: 100BASE-TX | Auto MDI/MDI-X: Yes | Packet buffer memory: 1.5 MB | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Cable types supported: Cat5 | Rack mounting: No | Cable types supported: Cat5e |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

GARP VLAN Registration Protocol (GVRP): Yes | Auto-negotiation: Yes | Multicast support: Yes | MAC address table: 4096 entries | Width: 158 mm | Cable types supported: Cat3 | Switch layer: L2 | Power consumption (max): 3.3 W | IGMP snooping: Yes | Full duplex: Yes | Cables included: AC | Height: 25 mm | MAC address auto-aging supported: Yes | User guide: Yes | Quality of Service (QoS) support: Yes | Harmonized System (HS) code: 85176990 | Flow control support: Yes | 10G support: No | Switch type: Unmanaged | Networking standards: IEEE 802.3x | AC input frequency: 50 Hz | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | AC input voltage: 220 V | Package type: Box | Quick start guide: Yes | LED indicators: Yes | Operating temperature (T-T): 0 - 40 °C | Power over Ethernet (PoE): No | Input current: 0.6 A | Product colour: Black | Storage temperature (T-T): -40 - 70 °C

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950