



TP-Link TL-SG1016PE network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Model: TL-SG1016PE

Manufacturer: TP-LINK

EAN: 1210002616775

Product Code: 1012522

R3,724

Certification: FCC, CE, RoHS | Networking standards: IEEE 802.3ad | Web-based management: Yes |
Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards:
IEEE 802.1p | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking
standards: IEEE 802.3u | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3at |
LED indicators: Yes | AC input voltage: 100 - 240 V | Operating temperature (T-T): 0 - 40 °C | AC input
frequency: 50 - 60 Hz | Product colour: Black | Power over Ethernet (PoE): Yes | Storage temperature

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

(T-T): -40 - 70 °C | Switch layer: L2 | Total Power over Ethernet (PoE) budget: 150 W | Switch type: Managed | Copper ethernet cabling technology: 100BASE-TX | Number of fans: 1 fan(s) | Jumbo frames support: Yes | Number of queues: 4 | Cable types supported: Cat5 | Cable types supported: Cat5e | Gigabit Ethernet (copper) ports quantity: 16 | Static port security: Yes | Throughput: 23.8 Mpps | Jumbo frames: 10000 | Store-and-forward: Yes | Copper ethernet cabling technology: 1000BASE-T | Copper ethernet cabling technology: 10BASE-T | Storage relative humidity (H-H): 5 - 90% | Operating relative humidity (H-H): 10 - 90% | Cable types supported: Cat3 | Power supply included: Yes | Height: 44 mm | Depth: 180 mm | Stackable: No | Virtual LAN features: Tagged VLAN | IGMP snooping: Yes | Virtual LAN features: Port-based VLAN | MAC address table: 8000 entries | Auto-negotiation: Yes | Harmonized System (HS) code: 85176990 | Full duplex: Yes | Power consumption (max): 124.4 W | Power over Ethernet plus (PoE+) ports quantity: 8 | Broadcast storm control: Yes | Basic switching RJ-45 Ethernet ports quantity: 16 | Loop protection: Yes | VLAN support: Yes | Switching capacity: 32 Gbit/s | Link aggregation: Yes | Cable types supported: Cat4 | Cables included: AC | Rate limiting: Yes | Port mirroring: Yes | Cable types supported: Cat6 | Auto MDI/MDI-X: Yes | Rack mounting: Yes | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Width: 294 mm | Flow control support: Yes | 10G support: No | Number of VLANs: 4000 | Rack mount kit: Yes | Quality of Service (QoS) support: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950