



TP-Link Omada 28-Port Gigabit L2+ Managed Switch with 24- Port PoE+



Model: TL-SG3428MP

Manufacturer: TP-LINK

EAN: 1210002611909

Product Code: 1017584

R8,869

Certification: CE, FCC, RoHS | Spanning tree protocol: Yes | Virtual LAN features: MAC address-based VLAN | Virtual LAN features: Tagged VLAN | Virtual LAN features: Voice VLAN | Power supply included: Yes | Package width: 440 mm | Basic switching RJ-45 Ethernet ports quantity: 24 | Security algorithms: SSH | Quick start guide: Yes | Store-and-forward: Yes | Link aggregation: Yes | Operating temperature (T-T): 0 - 45 °C | SFP module slots quantity: 4 | Height: 44 mm | Power consumption (max): 463.8 W | Gigabit Ethernet (copper) ports quantity: 24 | Rate limiting: Yes | System event log: Yes | Broadcast storm control: Yes | Jumbo frames: 9000 | Networking standards: IEEE 802.3af | Number of fans: 2 fan(s) | Package weight: 6.08 kg | Switch layer: L2+ | Jumbo frames support: Yes | Storage relative humidity (H-H): 5 - 90% | Management protocols: SNMPv1/v2c/v3, LLDP/LLDP-MED | Virtual LAN features: Private VLAN | Packet buffer memory: 12 MB | Harmonized System (HS) code: 85176990 | Width: 440 mm | Multicast support: Yes | Form factor: 1U | VLAN support: Yes | Power source: AC | Loop protection: Yes | Rack mounting: Yes | Power over Ethernet (PoE): Yes | Virtual LAN

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

features: Port-based VLAN | Operating relative humidity (H-H): 10 - 90% | Depth: 330 mm | DHCP features: DHCP client | DHCP features: DHCP relay | DHCP features: DHCP snooping | GARP VLAN Registration Protocol (GVRP): Yes | Total Power over Ethernet (PoE) budget: 384 W | Port mirroring: Yes | LED indicators: Yes | Console port: RJ-45/Micro-USB | Cloud-managed: Yes | IGMP snooping: Yes | BPDU filtering/protection: Yes | Configuring Location Settings (CLI): Yes | DHCP features: DHCPv6 client | ARP inspection: Yes | Access Control List (ACL): Yes | Copper ethernet cabling technology: 1000BASE-T | Head-of-line (HOL) blocking: Yes | Power connector: AC-in jack | Power over Ethernet plus (PoE+) ports quantity: 24 | Forwarding rate: 41.66 Mpps | Switch type: Managed | Active link detection: Yes | Networking standards: IEEE 802.3at | Static port security: Yes | Package height: 100 mm | IP routing: Yes | AC input voltage: 100 - 240 V | DHCP features: DHCPv6 snooping | Authentication: MAC-based authentication, Port-based authentication | MAC address table: 16000 entries | Web-based management: Yes | MAC address filtering: Yes | DHCP features: DHCP server | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.3u | Copper ethernet cabling technology: 10BASE-T | Networking standards: IEEE 802.3z | AC input frequency: 50/60 Hz | IP-MAC-Port binding: Yes | Ethernet LAN data rates: 10,100,1000 Mbit/s | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Security algorithms: SSL/TLS | Switching capacity: 56 Gbit/s | Networking standards: IEEE 802.3i | Package depth: 528 mm | User guide: Yes | Product colour: Black | Number of VLANs: 4000 | Flow control support: Yes | 10G support: No | SSH/SSL support: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950