



TP-Link 5-Port Gigabit Desktop PoE Switch with 4-Port



Model: TL-SG1005P

Manufacturer: TP-LINK

EAN: 1210002616607

Product Code: 1017585

R1,431

Certification: FCC, CE, RoHS | Cable types supported: Cat6 | AC input voltage: 100 - 220 V | Power consumption (max): 64.44 W | Operating relative humidity (H-H): 10 - 90% | Operating temperature (T-T): 0 - 40 °C | Stackable: No | Copper ethernet cabling technology: 100BASE-TX | Quick start guide: Yes | DC input voltage: 48 V | Networking standards: IEEE 802.3u | Cable types supported: Cat4 | IGMP snooping: Yes | Auto-negotiation: Yes | MAC address auto-aging supported: Yes | Networking standards: IEEE 802.3x | Storage relative humidity (H-H): 5 - 90% | AC input frequency: 50 Hz | Compliance certificates: Federal Communications Commission (FCC) | Total Power over Ethernet (PoE) budget: 56 W | Networking standards: IEEE 802.3af | Auto MDI/MDI-X: Yes | Power over Ethernet (PoE) ports quantity: 4 | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.1p | Switching capacity: 10 Gbit/s | Manual: Yes | MAC address table: 2000 entries | Package width: 131 mm | Copper ethernet cabling technology: 1000BASE-T | MAC address auto-learning supported: Yes | Cable types supported: Cat3 | Power source: DC/PoE | Cable types supported: Cat5 | Cable types supported: Cat5e | VLAN support: Yes | Basic switching RJ-45 Ethernet ports quantity: 5 | Copper ethernet cabling technology: 10BASE-T | Package type: Box | Package

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

height: 121 mm | Package weight: 761 g | Fanless: Yes | Height: 25 mm | Cables included: AC | Width: 99.8 mm | Rack mounting: No | Store-and-forward: Yes | Gigabit Ethernet (copper) ports quantity: 5 | LED indicators: Yes | Heat dissipation: 219.87 BTU/h | Switch type: Unmanaged | Input current: 1.25 A | Power supply included: Yes | Harmonized System (HS) code: 85176990 | Maximum cable length: 100 m | Forwarding rate: 7.44 Mpps | Compliance certificates: RoHS | Compliance certificates: CE | Depth: 98 mm | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Power over Ethernet (PoE): Yes | Sustainability compliance: Yes | 10G support: No | Package depth: 196 mm | Flow control support: Yes | AC adapter included: Yes | Product colour: Black | User guide: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950