Lindy 100m Cat.6 HDMI 4K60, Audio, IR and RS-232 HDBaseT Transmitter

Model: 38341

Manufacturer: LINDY

EAN: 4002888383417

Product Code: 1036798

R5,988

The Lindy 100m Cat.6 HDMI 4K60, Audio, IR and RS-232 HDBaseT Transmitter is one part of a high performance, reliable solution for extending HDMI signals over long distances via Cat.6 network cable. By combining this transmitter unit with a compatible Lindy HDBaseT receiver (i.e 38342), this solution ensures reliable transmission up to 100m.

The following distance and resolution combinations are possible when using high quality Cat.6 U/UTP or F/UTP cable:100m: 1920x1080@60Hz 4:4:4 8bit70m: 3840x2160@60Hz 4:4:4 8bit / 4:2:2 12bit

Supporting resolutions up to 4K Ultra HD, video can be viewed in stunning clarity, while additional support for HDR (High Dynamic Range) allows content to be displayed with enhanced brightness, greater contrasts of blacks and whites and a much wider colour gamut. This provides a reliable

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

solution for creating eye-catching digital signage in retail, immersive displays at events or engaging setups in larger conference rooms or lectures halls.

ARC support over HDMI allows for audio content to be returned from the display to a connected amplifier or soundbar, while local audio extraction allows for the connection of audio outputs for immersive multi-channel audio. Digital audio embedding at the receiver side can also be used for source audio, which can easily be switching via the push button on the main unit.

PoC (Power over Cable) functionality provides additional flexibility. This allows power to be supplied alongside data through Cat.6 network cable in a point-to-point connection between the transmitter and receiver, meaning only a single power supply is required at the transmitter unit. Ideal when power outlets are limited at the receiver end of the installation.

Featuring bi-directional IR ports at both sides of the setup, the source equipment can be easily controlled from the display side, and the display can also be controlled from the HDMI source side. Combined with CEC control, which allows commands from one main remote, this extension system allows for complete and simple control for the user. Bi-directional RS-232 and Ethernet ports also allow for integration into larger control systems, or connection to network switches and hubs with LAN access.

In addition, the power supply is connected via a screw type DC jack, providing a more secure and reliable connection, perfect for professional installations where accidental disconnections could create a major issue.

HDBaseT is a globally recognised standard for high quality distribution of AV content and other technologies, including power and control, over longer distances via low cost Cat.6 or above cable.

HDBaseT and the HDBaseT Alliance logo are trademarks of the HDBaseT Alliance.able. Using a different cable type, introducing wall plates, couplers or patch panels will result in a reduction of possible distances.

Please Note: This product uses the DSC method of compression to achieve 18G resolutions. If using another 18G HDBaseT product combined with this, please ensure both products support the same compression type.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950