



Lindy 150m Cat.6 HDMI 4K60, IR and RS- 232 HDBaseT Extender

Model: 38217

Manufacturer: LINDY

EAN: 4002888382175

Product Code: 1036799

R7,664

The Lindy C6 HDBaseT HDMI 18G and IR Extender is a complete high performance solution for extending HDMI signals over long distances via Cat.6 network cable. Combined this extender provides high quality content distribution up to distances of 150m.

The following distance and resolution combinations are possible when using high quality Cat.6 U/UTP or F/UTP cable: 150m (492.12ft) - 1280x720@60Hz via Long Reach Mode 100m (328.08ft) - 3840x2160@30Hz 4:4:4 8bit 70m (229.66ft) - 3840x2160@60Hz 4:4:4 8bit

Supporting resolutions up to 4K UHD 3840x2160@60Hz, video can be viewed in stunning clarity, while additional support for HDR (High Dynamic Range) allows content to be displayed with enhanced brightness, greater contrasts of blacks and whites and a much wider colour gamut. This provides a reliable solution for creating eye-catching digital signage in retail, immersive displays at

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

events or engaging setups in larger conference rooms or lectures halls. An HDMI loop out port provides additional capability for connecting a local display for monitoring of the video content in security or close-range distribution in residential installs, while simultaneously extending the signal to the receiver.

PoC (Power over Cable) functionality provides additional flexibility. This allows power to be supplied alongside data through Cat.6 network cable in a point to point connection between the transmitter and receiver, meaning only a single power supply is required at the transmitter unit. Ideal when power outlets are limited at the receiver end of the installation.

Featuring bi-directional IR ports at both sides of the setup, the source equipment can be easily controlled from the display side, and the display can also be controlled from the HDMI source side. Combined with CEC control, which allows commands from one main remote, this extension system allows for complete and simple control for the user.

Terminal blocks allows for pass-through of RS-232 commands when integrated into control systems.

HDBaseT is a globally recognised standard for high quality distribution of AV content and other technologies, including power and control, over longer distances via low cost Cat.6 or above cable.

HDBaseT and the HDBaseT Alliance logo are trademarks of the HDBaseT Alliance.

Please Note: This product uses the DSC method of compression to achieve 18G resolutions. If using another 18G HDBaseT product combined with this, please ensure both products support the same compression type.