



Lindy 100m Cat.6A 2 Host USB 3.2 Gen 1 HDBaseT Extender

Model: 43421

Manufacturer: LINDY

EAN: 4002888434218

Product Code: 1050653

R8,628

This Lindy USB 3.2 Gen 1 HDBaseT Extender can be used to extend the distance between USB peripheral devices and 2 host computers by up to 100m. Supports multiple USB signals, control, bulk, interrupt and isochronous data transfer.

A standard Cat.6A or above network cable* (not included) is used to bridge the connection between the transmitter and the receiver unit at the maximum supported distance of 100m (328.08ft). It's also possible to reach up to 40m using a Cat.6 cable.

The Extender features Power over Cable, which requires a single power supply only to be connected either to the transmitter unit or to the receiver unit. The Transmitter has 2 switchable host ports, one Type C and one Type B, with additional local device ports; 4 ports on the Receiver can provide 5V power as well to the connected devices: 2 Type A ports support up to 1.5A each, 1 Type A and 1

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Type C ports support up to 1A each.

Status LEDs help the user to check power, link between Transmitter and Receiver and if data transfer is running while additional RS232 and FSYNC GPIO pass-through ports allow sending bi-directional commands also for industrial cameras. It's also possible to control the extender via API commands.

With robust metal housing and mounting brackets, this Extender is the ideal solution for professional applications and industrial environments.

In addition, the power supply is connected via a screw type DC jack, providing a more secure and reliable connection, perfect for professional installations where accidental disconnections could create a major issue.

*: To cover long distances close to the 100m limit, we recommend using HDBaseT-certified Cat.6A (or above) cables.

This extender is certified by HDBaseT Alliance.

HDBaseT is a globally recognised standard for high quality distribution of AV content and other technologies, including power and control, over longer distances via low cost Cat.6 or above cable.

HDBaseT Trade Mark and the HDBaseT Alliance logo are trademarks of the HDBaseT Alliance. Using a different cable type, introducing wall plates, couplers or patch panels will result in a reduction of possible distances.