

**StarTech.com
Industrial Single
Port Gigabit PoE
Extender - 60W
802.3bt PoE
/PoE+/ PoE++ -
100m/ 330ft -
Power Over
Ethernet
Network Range
Extender - IP-30
- -40C to +75C -
TAA**



Model: POEEXT1G60W

Manufacturer: STARTECH

EAN: 065030889650

Product Code: 1053342

R5,092

Rugged PoE Extender | 60 Watts | IP-30 Aluminum Housing | 100m (330ft)

Extend the Reach of PoE Links up to 328 Feet

Extends the reach of PoE links up to 328' (100 m) to power powered devices (PD) over long distances; up to 4 extenders can be cascaded to extend the range of a PoE source (PSE) device up to an additional 400m, for a total range of 500m from the original PSE source to the target device.

Using Cat 5e (or higher rated) Ethernet cabling, it supports IEEE 802.3af (PoE / Type 1), IEEE 802.3at (PoE+ / Type 2), and IEEE 802.3bt (PoE++ / Type 3) to support PD devices like pan and tilt cameras, lighting, sensors, and wi-fi access points.

Designed for Harsh Environments

This PoE extender features IP-30 housing and an MTBF is 500,000+ hrs (Telcordia/Bellcore) at 50C, for long-term reliability and durability. Operating temp of -40C to 75C permits use in a wide range of indoor and outdoor applications that are not temperature controlled.

Rated to various vibration, shock, and free-fall standards:

- Vibration: EN 60068-2-6
- Shock: EN 60068-2-27
- Free-Fall: EN 60068-2-32

PoE Extender also includes hardware for mounting to the DIN rail or wall.

Flexible Power Outputs

Accepts inputs up to 95W from a PSE source and can provide 15W, 30W, or 60W of power output to a target PD device. Low 2.7W power consumption provides more power for devices, especially when multiple extenders are used for a single extension.

Features ESD, EFT, and surge protection at the following standards:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- ESD: IEC 61000-4-2: Contact: 6KV; Air: 8KV
- EFT: IEC 61000-4-4: Power: 2KV; Signal: 2KV
- Surge: IEC 61000-4-5: Power: 2KV; Signal: 2KV

POEEXT1G60W is backed by a StarTech.com two-year warranty and free lifetime technical support.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950