

MIKROTIK CCR2004-16G-2S+ CLOUD CORE ROUTER 4x1.7GHZ 128MB NAND 2x 10GE SFP+ 16x 1GE PORTS 2x AC INPUTS L6



MIKROTIK CCR2004-16G- 2S+ CLOUD CORE ROUTER 4x1.7GHZ 128MB NAND 2x 10GE SFP+ 16x 1GE PORTS 2x AC INPUTS L6

Model: CCR2004-16G-2S+

Manufacturer: MIKROTIK

EAN: 4752224007704

Product Code: 1064700

R10,017

Like the other models in CCR2004 series, this CCR also features the Annapurna Labs Alpine v2 CPU with 4x 64-bit ARMv8-A Cortex-A57 cores running at 1,7GHz. But here's the difference. This powerful router crushes all previous CCR models in single-core performance, and that is the most important aspect when it comes to heavy operations based on per-connection processing. Like queues, for example. But that's not all! It also has the best single-core performance per watt and best overall performance per watt among all the CCR devices. Better for the planet, better for the bills, it's a win-

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

win!

The router has 18 wired ports, including 16x Gigabit Ethernet ports and two 10G SFP+ cages. It also has a full-size USB and RJ-45 console port on the front panel. Like all CCR devices, it comes in a classic white 1U rackmount case. Built-in dual redundant power supplies are included, so you have one less thing to worry about. And, of course, there is active cooling to keep things nice and cool. Each group of 8 Gigabit Ethernet ports is connected to a separate Marvell Amethyst family switch-chip. Each switch chip has a 10 Gbps full-duplex line connected to the CPU. The same goes for each SFP+ cage - a separate 10 Gbps full-duplex line.

Product Description: MikroTik Cloud Core Router CCR2004-16G-2S+ - router - rack-mountable |

Device Type: Router | Enclosure Type: Rack-mountable | Data Link Protocol: Ethernet, Fast Ethernet, Gigabit Ethernet, 10 Gigabit Ethernet | Power: AC 100-240 V (50/60 Hz)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950