



Teltonika RUT901, router



Model: RUT901000000

Manufacturer: TELTONIKA

EAN: 4779051840823

Product Code: 1087921

R3,669

Produktbeschreibung Der Mobilfunk-Router RUT901 bringt die erstklassigen Funktionen seiner Vorgänger RUT950 und RUT951 auf den Markt. Das Gerät gewährleistet eine hohe Leistung und bietet ein automatisches WAN-Failover auf eine verfügbare Backup-Verbindung, wodurch die Kontinuität des Netzwerks gewährleistet und Ausfallzeiten vermieden werden. Art.-Nr.: 100137475
Typ: Router | EAN: 4779051840823 | Hersteller-Nr.: RUT901000000 | Bauform: Desktop | Einsatzbereich: Business | Anschlüsse: 4x (davon: 4x 10/100) | WLAN: Wi-Fi 3 (802.11b), Wi-Fi 3 (802.11g), Wi-Fi 4 (802.11n) - (2.4 GHz) | Mobilfunkstandards: 3G/UMTS, 4G/LTE | Hardware: Mediatek, 580 MHz, MIPS 24KEc | Speicherkarten: mini-SIM-Karte | LEDs: Power, LAN-Link LEDs: 4x | Feature: Mobile Features: SIM switch, Status, SMS, Black/White list, Band management, APN, Bridge, Passthrough | Netzwerk Protokolle: VoIP passthrough support, Connection monitoring, Firewall, DHCP, QoS / Smart Queue | Management (SQM), DDNS, Network backup, Load balancing, SSHFS | TCP, UDP, IPv4, IPv6, ICMP, NTP, DNS, HTTP, HTTPS, FTP, SMTP, SSL v3, TLS, ARP, VRRP, PPP, PPPoE, UPNP, SSH, DHCP, Telnet, SMPP, SMNP, MQTT, Wake On Lan (WOL) | Authentication, Firewall, Attack prevention, VLAN, Mobile quota control, WEB filter, Access control | Static routing, Dynamic routing (BGP, OSPF v2, RIP v1/v2, NHRP) | OpenVPN, IPsec, GRE, PPTP, L2TP, Stunnel, DMVPN, SSTP, ZeroTier, WireGuard | Monitoring und Management: WEB UI, FOTA, SSH, SMS, Call, TR-069, MQTT, SNMP, JSON-RPC, MODBUS, RMS | Ping Reboot, Wget Reboot, Periodic Reboot, LCP and ICMP for link

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

inspection | Cloud: RMS, Cloud of Things, ThingWorx, Cumulocity, Azure IoT Hub | Hotspot: Captive portal (Hotspot), internal/external Radius server, built in customizable landing page | SMS Features: SMS status, SMS configuration, send/read SMS via HTTP POST/GET, EMAIL to SMS, SMS to EMAIL, SMS to HTTP, SMS to SMS, scheduled SMS, SMS autoreply, SMPP | Weitere Informationen: 4-pin power socket, 9-30 VD | 2 x SIM slots (Mini SIM - 2FF), 1.8 V/3 V, external SIM holders, eSIM (Optional) | 2 x SMA für LTE, 2 x RP-SMA für WiFi Antennen | IEEE 802.11b/g/n, Access Point (AP), Station (STA) | Hinweis: RutOS (OpenWrt based Linux OS) | Abmessungen: Breite: 110 mm x Höhe: 50 mm x Tiefe/Länge: 100 mm | Gewicht: 297 Gramm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950