



NETGEAR 8PT GE Plus Switch W/POE+



Model: GS308EP-100PES

Manufacturer: NETGEAR

EAN: 606449153040

Product Code: 1090331

R2,959

NETGEAR Plus Switches with PoE meets business networks growing need by providing fundamental network features such as simplified VLANs, QoS set-up and IGMP Snooping that will help optimize the performance of business networks. Plus Switches are the perfect upgrade from the plug-and-play unmanaged switch, delivering essential networking features at a very affordable price. The GS305EP/GS305EPP with 4-port PoE+ and GS308EP/GS308EPP with 8-port PoE+ models support Power-over-Ethernet (PoE) and can power devices such as VoIP phones, surveillance IP cameras, wireless access points and many other applications. These Plus switches models include uninterruptable PoE to help optimize the performance and troubleshooting of business networks. The improved business-friendly GUI allows easy management and simple configuration. With the growing deployment of applications and an all-in-one solution, providing management and power to these applications would be ideal.

Product Description: NETGEAR Plus GS308EP - switch - 8 ports - smart | Device Type: Switch - 8 ports - smart | Subtype: Gigabit Ethernet | Ports: 8 x 10/100/1000 (PoE+) | Power Over Ethernet (PoE): PoE+ | PoE Budget: 62 W | Performance: Bandwidth: 16 Gbps | Capacity: VLANs supported: 64 Multicast groups: 128 | MAC Address Table Size: 4K entries | Jumbo Frame Support: 9216 bytes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Routing Protocol: IGMP, IGMPv2, IGMPv3 | Remote Management Protocol: DHCP | Features: QoS, IGMP snooping, DoS attack prevention, loopback detection, port mirroring, fanless, auto-uplink (auto MDI/MDI-X), store and forward, 192KB packet buffer, EEE, WRR, VLAN support, VLAN Tagging, port-based VLAN, Link Aggregation, port trunking, block unknown multicast, DHCP client, rate limit, DSCP support, CoS, full duplex mode, flow control, password protection, cable test | Compliant Standards: IEEE 802.3at, IEEE 802.3az, IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3af | Dimensions (WxDxH): 15.8 cm x 10.1 cm x 2.7 cm | Weight: 490 g | Manufacturer Warranty: 5-year warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950