



TP-Link 4G+ AX1800 Whole Home Mesh WiFi 6 Gateway



Model: DECO X20-4G

Manufacturer: TP-LINK

EAN: 6935364006709

Product Code: 1094499

R4,225

Supported WAN type: Dynamic IP/Static IP/PPPoE/L2TP/PPTP | Certification: CE, RoHS | 3G standards: DC-HSPA+ | 3G standards: UMTS | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G standards: HSPA | Port forwarding: Yes | Cloud services supported: TP-Link ID | 4G standard: TD-LTE & FDD-LTE | Static IP: Yes | Number of guest networks (5 GHz): 1 | Transmit power: CE: ≤20 dBm (2.4GHz), ≤23 dBm (5GHz) | Ethernet cable: Yes | 4G bands supported: 900 | UMTS bands supported: 2100 MHz | 4G bands supported: 2100 | 4G bands supported: 800 | Number of guest networks (2.4 GHz): 1 | MU-MIMO technology: Yes | UMTS bands supported: 850 | Number of devices supported: 150 | 4G bands supported: 2600 | 4G bands supported: 850 | 4G bands supported: 2500 MHz | Guest access: Yes | Harmonized System (HS) code: 85171800 | 4G bands supported: 700 | 4G bands supported: 2300 | SIM card type: NanoSIM | Mobile network generation: 3G, 4G | 4G bands supported: 1800 | Supported network protocols (IPv6): Y | UMTS bands supported: 900 | Built-in processor: Yes | WLAN data transfer rate (first band): 574 Mbit/s | Dynamic DNS (DDNS): Yes | Operating modes: 3G/4G, Router, Access Point | Point-to-point protocol over Ethernet (PPPoE): Yes | WLAN data transfer rate (second band): 1201 Mbit/s | AC adapter input current: 0.6 A | Dynamic IP: Yes | Wi-Fi standards: Wi-Fi 5

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

(802.11ac) | Wi-Fi standards: Wi-Fi 4 (802.11n) | Operating temperature (T-T): 0 - 40 °C | Processor cores: 4 | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | MIMO: Yes | Quality of Service (QoS) support: Yes | Number of products included: 1 pc(s) | AC adapter output voltage: 12 V | Wi-Fi standards: 802.11b | Wi-Fi standards: 802.11g | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Product colour: White | AC adapter included: Yes | Storage temperature (T-T): -40 - 60 °C | Package weight: 1.22 kg | Package depth: 213.5 mm | Reset button: Yes | Security algorithms: WPA-PSK | Security algorithms: WPA3 | Storage relative humidity (H-H): 5 - 90% | Antenna type: Internal | Ethernet LAN (RJ-45) ports: 3 | Networking standards: IEEE 802.11ax | Security algorithms: WPA | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Operating relative humidity (H-H): 10 - 90% | AC input voltage: 100 - 240 V | Width: 105 mm | LED indicators: Power | Processor frequency: 1.5 GHz | Ethernet WAN: Yes | Networking standards: IEEE 802.11a | Package width: 241 mm | AC adapter output current: 1.5 A | AC input frequency: 50/60 Hz | Package height: 124 mm | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11b | DC-in jack: Yes | Antennas quantity: 4 | Height: 167 mm | Warnings: Do not open the appliance housing - risk of electric shock. | Warnings: Avoid contact with liquids as this may cause electric shock. | Warnings: The product may emit radio waves that may interfere with other electronic devices. | Depth: 105 mm | Number of units included: 1 pc(s)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950