



TP-Link TL-MR100 wireless router Fast Ethernet Single-band (2.4 GHz) 4G Black



Model: TL-MR100

Manufacturer: TP-LINK

EAN: 1210002609258

Product Code: 1106088

R1,704

Receiver sensitivity: 11g 54M: -74dBm 11n HT20: -71dBm 11n HT40: -67dBm | Certification: CE, RoHS | Browser supported: Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 | WLAN data transfer rate (max): 300 Mbit/s | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | Wi-Fi standards: 802.11b | WAN connection type: RJ-45 | Antennas quantity: 2 | Output voltage: 9 V | Wi-Fi standards: 802.11g | Wi-Fi standards: Wi-Fi 4 (802.11n) | Height: 36 mm | Cabling technology: 10/100Base-T(X) | Port forwarding: Yes | Harmonized System (HS) code: 85176990 | Ethernet LAN interface type: Fast Ethernet | DMZ support: Yes | Ethernet LAN: Yes | Port triggering: Yes | 4G standard: LTE-TDD & LTE-FDD | Equivalent Isotropically Radiated Power (EIRP) (@IEEE 802.11n): 20 dBmW | Dynamic DNS (DDNS): Yes | Supported network protocols: IPv4, IPv6 | 4G bands supported: 2600 MHz | 4G bands supported: 2500 | Guest access: Yes | Output current: 0.85 A | Depth: 114 mm | DHCP server: Yes | USB port: No | IP address filtering: Yes | SIM card slot: Yes | On/off switch: Yes | SIM card type:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

MicroSIM | WPS push button: Yes | 4G bands supported: 900 | 4G bands supported: 2300 | 4G bands supported: 1800 | 4G bands supported: 1900 | 4G bands supported: 2100 | 4G bands supported: 800 | Width: 154 mm | Package height: 66 mm | 3G/4G USB modem compatibility: No | Ethernet WAN: Yes | 3G standards: UMTS | Mobile network generation: 4G | Product type: Tabletop router | Firewall: Yes | Universal Plug and Play (UPnP): Yes | Quick installation guide: Yes | 3G standards: HSPA | 3G bands supported: 900 | Memory card slot(s): No | 3G bands supported: 2100 MHz | Wi-Fi band: Single-band (2.4 GHz) | Wi-Fi Multimedia (WMM)/(WME): Yes | 3G bands supported: 850 | Linux operating systems supported: Yes | Wireless statistics: Yes | Wireless radio: Yes | Schedule access: Yes | Antenna design: External | 4G: Yes | Security algorithms: WPA | Stateful Packet Inspection (SPI): Yes | Networking standards: IEEE 802.11b | Windows operating systems supported: Windows 98SE | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Windows operating systems supported: Windows XP | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Windows operating systems supported: Windows NT | Package depth: 161 mm | MAC address filtering: Yes | 3G: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | AC adapter included: Yes | Operating relative humidity (H-H): 10 - 90% | Security algorithms: 128-bit WEP | Windows operating systems supported: Windows 8 | Weight: 150 g | Package weight: 480 g | Windows operating systems supported: Windows 2000 | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | Mac operating systems supported: Yes | Windows operating systems supported: Windows 7 | Ethernet LAN data rates: 100 | Antenna connector type: N-type | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Security algorithms: WPA2-PSK | Product colour: Black | Cables included: LAN (RJ-45) | DC-in jack: Yes | Reset button: Yes | Package width: 293 mm | Ethernet LAN (RJ-45) ports: 2 | Operating temperature (T-T): 0 - 40 °C | DHCP client: Yes | Power source type: DC

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950