



TP-Link 5-Port Gigabit Easy Smart PoE Switch with 4- Port PoE+



Model: TL-SG105PE

Manufacturer: TP-LINK

EAN: 1210002616850

Product Code: 1106107

R1,574

Certification: FCC, CE, RoHS | Harmonized System (HS) code: 85176990 | Width: 99.8 mm | Rack mounting: No | Basic switching RJ-45 Ethernet ports quantity: 5 | Copper ethernet cabling technology: 100BASE-TX | Total Power over Ethernet (PoE) budget: 65 W | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-FX | Switching capacity: 10 Gbit/s | Package height: 121 mm | Jumbo frames support: Yes | Power source: DC | 10G support: No | User guide: Yes | VLAN support: Yes | Height: 25 mm | Auto MDI/MDI-X: Yes | Copper ethernet cabling technology: 1000BASE-T | Power supply included: Yes | Depth: 98 mm | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Switch layer: L2 | Virtual LAN features: Port-based VLAN | Virtual LAN features: Tagged VLAN | Store-and-forward: Yes | Forwarding rate: 7.44 Mpps | Link aggregation: Yes | Rate limiting: Yes | Cable types supported: Cat5 | Cable types supported: Cat5e | Cable types supported: Cat3 | Cable types supported: Cat4 | Cable types supported: Cat6 | Broadcast storm control: Yes | Loop protection: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Gigabit Ethernet (copper) ports quantity: 5 | Power over Ethernet plus (PoE+) ports quantity: 4 | Packet buffer memory: 1 MB | Number of queues: 4 | Switch type: Managed | Auto-negotiation: Yes | IGMP snooping: Yes | Flow control support: Yes | MAC address table: 2000 entries | Port mirroring: Yes | Jumbo frames: 16000 | Heat dissipation: 256.3 BTU/h | Number of VLANs: 4000 | Fanless: Yes | Input voltage: 53.5 V | Power over Ethernet (PoE): Yes | LED indicators: Link | Power consumption (max): 75.16 W | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Package weight: 770 g | Operating relative humidity (H-H): 10 - 90% | Operating temperature (T-T): 0 - 40 °C | Package width: 131 mm | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Storage relative humidity (H-H): 5 - 95% | Web-based management: Yes | Networking standards: IEEE 802.3i | Input current: 1.31 A | LED indicators: Activity | LED indicators: PoE | Package depth: 196 mm | LED indicators: Power | Product colour: Black | LED indicators: Speed | Networking standards: IEEE 802.3u | LED indicators: Status | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950