



TP-Link Omada 24-Port Gigabit L2+ Managed Switch with 4 SFP Slots



Model: SG3428

Manufacturer: TP-LINK

EAN: 1210002611886

Product Code: 1106108

R4,985

Power consumption (max): 20.6 W | Depth: 180 mm | Jumbo frames support: Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | Power source: AC | Cables included: LAN (RJ-45) | Rack mounting: Yes | Power over Ethernet (PoE): No | Width: 440 mm | VLAN support: Yes | Height: 44 mm | 10G support: No | Operating temperature (T-T): 0 - 45 °C | Operating relative humidity (H-H): 10 - 90% | Power supply included: No | Form factor: 1U | Number of fans: 0 fan(s) | Number of VLANs: 4000 | Switching capacity: 56 Gbit/s | Storage relative humidity (H-H): 5 - 90% | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Multicast support: Yes | SFP module slots quantity: 4 | IGMP snooping: Yes | Packet buffer memory: 12 MB | Switch type: Managed | DHCP features: DHCP client | DHCP features: DHCP relay | DHCP features: DHCP snooping | Heat dissipation: 70.3 BTU/h | Port mirroring: Yes | DHCP features: DHCPv6 snooping | DHCP features: DHCPv6 client | DHCP features: DHCP server | MAC address table: 16000 entries | IPv6 routes: 48 | IPv4 routes: 48 | IPv4 & IPv6 features: IPv6

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

tracert | IPv4 & IPv6 features: IPv6 Telnet | Ethernet LAN data rates: 10,100,1000 Mbit/s | IP-MAC-Port binding: Yes | IP routing: Yes | AC input voltage: 100 - 240 V | Quick start guide: Yes | Broadcast storm control: Yes | Multicast Listener Discovery (MLD) snooping: Y | IPv4 & IPv6 features: IPv6 ping | Switch layer: L2/L3 | Number of static routes: 48 | BPDU filtering/protection: Yes | Configuring Location Settings (CLI): Yes | Forwarding rate: 41.66 Mpps | Spanning tree protocol: Yes | Jumbo frames: 9000 | System event log: Yes | Link aggregation: Yes | Virtual LAN features: Private VLAN | Virtual LAN features: Voice VLAN | Virtual LAN features: Tagged VLAN | Authentication type: AAA, RADIUS, TACACS+ | Product colour: Black | IPv4 & IPv6 features: IPv4/IPv6 access-control list (ACL) | Gigabit Ethernet (copper) ports quantity: 24 | Web-based management: Yes | Flow control support: Yes | ARP inspection: Yes | Access Control List (ACL): Yes | Virtual LAN features: Protocol-based VLAN | Console port: RJ-45/Micro-USB | Cloud-managed: Yes | Policy-based routing: Yes | Authentication: MAC-based authentication, Port-based authentication | Networking standards: IEEE 802.3i | Store-and-forward: Yes | Loop protection: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.3u | MIB support: Yes | GARP VLAN Registration Protocol (GVRP): Yes | Static route: Yes | Head-of-line (HOL) blocking: Yes | LED indicators: Yes | Rate limiting: Yes | Networking standards: IEEE 802.3z | SSH/SSL support: Yes | AC input frequency: 50/60 Hz | Management protocols: SNMPv1/v2c/v3, SNMP | Static port security: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950