



TP-Link Omada 24-Port Gigabit and 4-Port 10GE SFP+ L2+ Managed Switch with 24-Port PoE+

Model: SG3428XMP

Manufacturer: TP-LINK

EAN: 1210002611619

Product Code: 1106316

R11,007

Operating relative humidity (H-H): 10 - 90% | Networking standards: IEEE 802.1s | Cables included: LAN (RJ-45) | Web-based management: Yes | Height: 44 mm | Power over Ethernet (PoE): Yes | Rack mounting: Yes | AC input voltage: 100 - 240 V | Power consumption (max): 486.2 W | Ethernet LAN data rates: 10,100,1000 Mbit/s | Storage relative humidity (H-H): 5 - 90% | LED indicators: Yes | Width: 440 mm | Networking standards: IEEE 802.1w | Power source: AC | Quick start guide: Yes | AC input frequency: 50/60 Hz | Networking standards: IEEE 802.11d | Depth: 330 mm | Operating temperature (T-T): 0 - 45 °C | Total Power over Ethernet (PoE) budget: 384 W | Form factor: 1U | Number of fans: 2 fan(s) | Product colour: Black | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | VLAN support: Yes | Multicast support: Yes | Virtual LAN features:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Protocol-based VLAN | Link aggregation: Yes | Packet buffer memory: 12 MB | Loop protection: Yes | Virtual LAN features: MAC address-based VLAN | DHCP features: DHCP client | DHCP features: DHCP relay | MAC address table: 16000 entries | DHCP features: DHCP server | Number of static routes: 48 | Gigabit Ethernet (copper) ports quantity: 24 | Switch layer: L2+ | Port mirroring: Yes | Switch type: Managed | Active link detection: Yes | Virtual LAN features: Voice VLAN | SSH/SSL support: Yes | 10G support: Yes | Spanning tree protocol: Yes | Jumbo frames: 9000 | BPDU filtering/protection: Yes | Heat dissipation: 1658.78 BTU/h | Flow control support: Yes | IP-MAC-Port binding: Yes | System event log: Yes | SFP+ module slots quantity: 4 | Access Control List (ACL): Yes | Virtual LAN features: Private VLAN | Rate limiting: Yes | DHCP features: DHCPv6 snooping | Broadcast storm control: Yes | DHCP features: DHCP snooping | Number of VLANs: 4000 | DHCP features: DHCPv6 client | Basic switching RJ-45 Ethernet ports quantity: 24 | Jumbo frames support: Yes | Virtual LAN features: Port-based VLAN | Head-of-line (HOL) blocking: Yes | Management protocols: SNMPv1/v2c/v3, SNTP | Virtual LAN features: Tagged VLAN | Policy-based routing: Yes | IGMP snooping: Yes | Console port: RJ-45/Micro-USB | Cloud-managed: Yes | Switching capacity: 128 Gbit/s | Power connector: AC-in jack | Power over Ethernet plus (PoE+) ports quantity: 24 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Power supply included: Yes | Forwarding rate: 95.23 Mpps | MIB support: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950