



TP-Link TL-SG108 network switch Unmanaged L2 Gigabit Ethernet (10/100/1000) Black



Model: TL-SG108

Manufacturer: TP-LINK

EAN: 1210002616898

Product Code: 1107823

R1,188

Certification: CE, FCC ,RoHS | Width: 158 mm | Storage relative humidity (H-H): 5 - 90% | Cable types supported: Cat4 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Rack mounting: No | IGMP snooping: Yes | Auto MDI/MDI-X: Yes | Packet buffer memory: 1.5 MB | Quality of Service (QoS) support: Yes | Multicast support: Yes | Auto-negotiation: Yes | 10G support: No | Cable types supported: Cat5 | Cable types supported: Cat5e | Depth: 101 mm | Wall mountable: Yes | User guide: Yes | Operating relative humidity (H-H): 10 - 90% | Forwarding rate: 11.9 Mpps | Power supply included: Yes | GARP VLAN Registration Protocol (GVRP): Yes | Power consumption (max): 3.3 W | Manual: Yes | Access Control List (ACL) IPv6 entries: 11 | Copper ethernet cabling technology: 100BASE-TX | Copper ethernet cabling technology: 10BASE-T | Switching capacity: 16 Gbit/s | Copper

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

ethernet cabling technology: 1000BASE-T | MAC address auto-learning supported: Yes | MAC address table: 4096 entries | Switch layer: L2 | Basic switching RJ-45 Ethernet ports quantity: 8 | Jumbo frames support: Yes | Jumbo frames: 16000 | Store-and-forward: Yes | Harmonized System (HS) code: 85176990 | Cable types supported: Cat3 | MAC address auto-aging supported: Yes | Flow control support: Yes | Switch type: Unmanaged | Full duplex: Yes | Height: 25 mm | Cables included: AC | Power over Ethernet (PoE): No | Package type: Box | Operating temperature (T-T): 0 - 40 °C | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Input current: 0.6 A | LED indicators: Yes | Product colour: Black | AC input frequency: 50 Hz | Quick start guide: Yes | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3x | Storage temperature (T-T): -40 - 70 °C | AC input voltage: 220 V

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950