



TP-Link TL-SG1016PE network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Model: TL-SG1016PE

Manufacturer: TP-LINK

EAN: 1210002616775

Product Code: 1108399

R3,724

Certification: FCC, CE, RoHS | AC input voltage: 100 - 240 V | LED indicators: Yes | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3at | AC input frequency: 50 - 60 Hz | Networking standards: IEEE 802.3af | Web-based management: Yes | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Storage temperature (T-T): -40 - 70 °C | Operating temperature (T-T): 0 - 40 °C | Product colour: Black |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Power over Ethernet (PoE): Yes | Auto MDI/MDI-X: Yes | Switching capacity: 32 Gbit/s | IGMP snooping: Yes | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Quality of Service (QoS) support: Yes | Rack mounting: Yes | Port mirroring: Yes | Width: 294 mm | Depth: 180 mm | MAC address table: 8000 entries | Storage relative humidity (H-H): 5 - 90% | Operating relative humidity (H-H): 10 - 90% | Power supply included: Yes | 10G support: No | Number of fans: 1 fan(s) | Jumbo frames support: Yes | Number of VLANs: 4000 | Total Power over Ethernet (PoE) budget: 150 W | Power consumption (max): 124.4 W | Harmonized System (HS) code: 85176990 | VLAN support: Yes | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-TX | Basic switching RJ-45 Ethernet ports quantity: 16 | Switch type: Managed | Copper ethernet cabling technology: 1000BASE-T | Height: 44 mm | Full duplex: Yes | Cables included: AC | Throughput: 23.8 Mpps | Store-and-forward: Yes | Link aggregation: Yes | Gigabit Ethernet (copper) ports quantity: 16 | Jumbo frames: 10000 | Broadcast storm control: Yes | Power over Ethernet plus (PoE+) ports quantity: 8 | Cable types supported: Cat6 | Cable types supported: Cat3 | Static port security: Yes | Cable types supported: Cat4 | Cable types supported: Cat5 | Cable types supported: Cat5e | Rate limiting: Yes | Stackable: No | Virtual LAN features: Tagged VLAN | Switch layer: L2 | Flow control support: Yes | Rack mount kit: Yes | Loop protection: Yes | Number of queues: 4 | Auto-negotiation: Yes | Virtual LAN features: Port-based VLAN

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950