



TP-Link Omada 28-Port Gigabit L2+ Managed Switch with 24- Port PoE+



Model: TL-SG3428MP

Manufacturer: TP-LINK

EAN: 1210002611909

Product Code: 1111439

R8,869

Certification: CE, FCC, RoHS | Copper ethernet cabling technology: 1000BASE-T | Head-of-line (HOL) blocking: Yes | Package height: 100 mm | Form factor: 1U | Depth: 330 mm | VLAN support: Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | Configuring Location Settings (CLI): Yes | Copper ethernet cabling technology: 10BASE-T | Storage relative humidity (H-H): 5 - 90% | Power source: AC | Multicast support: Yes | Virtual LAN features: Voice VLAN | Rate limiting: Yes | IP-MAC-Port binding: Yes | Ethernet LAN data rates: 10,100,1000 Mbit/s | Operating temperature (T-T): 0 - 45 °C | Virtual LAN features: Port-based VLAN | Virtual LAN features: Private VLAN | Virtual LAN features: MAC address-based VLAN | Total Power over Ethernet (PoE) budget: 384 W | Package width: 440 mm | Loop protection: Yes | DHCP features: DHCP snooping | DHCP features: DHCP client | DHCP features: DHCP relay | System event log: Yes | Switch layer: L2+ | Access Control List (ACL): Yes | Virtual LAN features: Tagged VLAN | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Switch type: Managed | Active link detection:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Yes | Networking standards: IEEE 802.3af | AC input voltage: 100 - 240 V | Security algorithms: SSH | Power consumption (max): 463.8 W | Quick start guide: Yes | Operating relative humidity (H-H): 10 - 90% | Power supply included: Yes | Networking standards: IEEE 802.3i | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.3ab | Gigabit Ethernet (copper) ports quantity: 24 | Networking standards: IEEE 802.3at | Power connector: AC-in jack | Power over Ethernet plus (PoE+) ports quantity: 24 | Forwarding rate: 41.66 Mpps | Broadcast storm control: Yes | Web-based management: Yes | MAC address filtering: Yes | DHCP features: DHCPv6 snooping | Number of fans: 2 fan(s) | IP routing: Yes | Spanning tree protocol: Yes | Jumbo frames: 9000 | Jumbo frames support: Yes | BPDU filtering/protection: Yes | Number of VLANs: 4000 | Link aggregation: Yes | Store-and-forward: Yes | Networking standards: IEEE 802.3u | Product colour: Black | Flow control support: Yes | Authentication: MAC-based authentication, Port-based authentication | Package weight: 6.08 kg | User guide: Yes | SSH/SSL support: Yes | Package depth: 528 mm | DHCP features: DHCPv6 client | ARP inspection: Yes | 10G support: No | LED indicators: Yes | DHCP features: DHCP server | Height: 44 mm | Management protocols: SNMPv1/v2c/v3, LLDP/LLDP-MED | Static port security: Yes | SFP module slots quantity: 4 | Security algorithms: SSL/TLS | AC input frequency: 50/60 Hz | Switching capacity: 56 Gbit/s | Power over Ethernet (PoE): Yes | Width: 440 mm | Rack mounting: Yes | Harmonized System (HS) code: 85176990 | IGMP snooping: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Port mirroring: Yes | GARP VLAN Registration Protocol (GVRP): Yes | Packet buffer memory: 12 MB | Console port: RJ-45/Micro-USB | Cloud-managed: Yes | MAC address table: 16000 entries

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950