



TP-Link 5-Port Gigabit Desktop PoE Switch with 4-Port



Model: TL-SG1005P

Manufacturer: TP-LINK

EAN: 1210002616607

Product Code: 1111440

R1,538

Certification: FCC, CE, RoHS | Operating relative humidity (H-H): 10 - 90% | Power supply included: Yes | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3x | Storage relative humidity (H-H): 5 - 90% | Switch type: Unmanaged | Cables included: AC | Power consumption (max): 64.44 W | LED indicators: Yes | Input current: 1.25 A | Networking standards: IEEE 802.3af | Storage temperature (T-T): -40 - 70 °C | AC input frequency: 50 Hz | Copper ethernet cabling technology: 100BASE-TX | AC input voltage: 100 - 220 V | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Product colour: Black | VLAN support: Yes | Manual: Yes | Copper ethernet cabling technology: 1000BASE-T | MAC address auto-learning supported: Yes | Package weight: 761 g | Quick start guide: Yes | Heat dissipation: 219.87 BTU/h | Basic switching RJ-45 Ethernet ports quantity: 5 | Copper ethernet cabling technology: 10BASE-T | Package depth: 196 mm | Flow control support: Yes | Quality of Service (QoS) support: Yes | Networking standards: IEEE 802.3u | Power over Ethernet (PoE): Yes | IGMP snooping: Yes | AC adapter included: Yes | User guide: Yes | Power over Ethernet (PoE) ports quantity: 4 | Height: 25 mm | MAC address table: 2000 entries | Auto-negotiation: Yes | MAC address auto-aging supported: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

DC input voltage: 48 V | Depth: 98 mm | Gigabit Ethernet (copper) ports quantity: 5 | Cable types supported: Cat3 | Stackable: No | Operating temperature (T-T): 0 - 40 °C | Cable types supported: Cat4 | Store-and-forward: Yes | Total Power over Ethernet (PoE) budget: 56 W | Cable types supported: Cat6 | Fanless: Yes | Power source: DC/PoE | Cable types supported: Cat5 | Cable types supported: Cat5e | 10G support: No | Harmonized System (HS) code: 85176990 | Switching capacity: 10 Gbit/s | Forwarding rate: 7.44 Mpps | Width: 99.8 mm | Rack mounting: No | Auto MDI/MDI-X: Yes | Package type: Box | Package height: 121 mm | Sustainability compliance: Yes | Maximum cable length: 100 m | Package width: 131 mm | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950