



TP-Link 4G+ AX1800 Whole Home Mesh WiFi 6 Gateway



Model: DECO X20-4G

Manufacturer: TP-LINK

EAN: 6935364006709

Product Code: 1111682

R4,221

Supported WAN type: Dynamic IP/Static IP/PPPoE/L2TP/PPTP | Certification: CE, RoHS | Dynamic IP: Yes | 3G standards: HSPA | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Ethernet cable: Yes | Dynamic DNS (DDNS): Yes | Port forwarding: Yes | Transmit power: CE: ≤20 dBm (2.4GHz), ≤23 dBm (5GHz) | Point-to-point protocol over Ethernet (PPPoE): Yes | UMTS bands supported: 2100 MHz | Static IP: Yes | 4G standard: TD-LTE & FDD-LTE | 3G standards: UMTS | Operating modes: 3G/4G, Router, Access Point | Built-in processor: Yes | Harmonized System (HS) code: 85171800 | SIM card type: NanoSIM | UMTS bands supported: 850 | Mobile network generation: 3G, 4G | Guest access: Yes | Number of guest networks (5 GHz): 1 | UMTS bands supported: 900 | WLAN data transfer rate (first band): 574 Mbit/s | 3G standards: DC-HSPA+ | AC adapter input current: 0.6 A | Number of devices supported: 150 | MU-MIMO technology: Yes | WLAN data transfer rate (second band): 1201 Mbit/s | 4G bands supported: 2600 | 4G bands supported: 850 | 4G bands supported: 2500 MHz | 4G bands supported: 700 | 4G bands supported: 2300 | 4G bands supported: 2100 | 4G bands supported: 800 | 4G bands supported: 1800 | Supported network protocols (IPv6): Y | Cloud services supported: TP-Link ID | 4G bands supported: 900 | Number of guest networks (2.4 GHz): 1 | Reset button: Yes | LED indicators:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Power | Networking standards: IEEE 802.11ax | AC input voltage: 100 - 240 V | AC adapter output current: 1.5 A | AC input frequency: 50/60 Hz | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | MIMO: Yes | Networking standards: IEEE 802.11a | Antenna type: Internal | AC adapter output voltage: 12 V | Networking standards: IEEE 802.11b | Product colour: White | DC-in jack: Yes | Networking standards: IEEE 802.11ac | Width: 105 mm | Antennas quantity: 4 | Wi-Fi standards: Wi-Fi 4 (802.11n) | Wi-Fi standards: 802.11g | Processor cores: 4 | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Depth: 105 mm | Package height: 124 mm | Package depth: 213.5 mm | Quality of Service (QoS) support: Yes | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Wi-Fi standards: 802.11b | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | AC adapter included: Yes | Storage temperature (T-T): -40 - 60 °C | Warnings: Avoid contact with liquids as this may cause electric shock. | Warnings: Do not open the appliance housing - risk of electric shock. | Security algorithms: WPA-PSK | Security algorithms: WPA3 | Storage relative humidity (H-H): 5 - 90% | Operating relative humidity (H-H): 10 - 90% | Warnings: The product may emit radio waves that may interfere with other electronic devices. | Number of products included: 1 pc(s) | Height: 167 mm | Package weight: 1.22 kg | Ethernet WAN: Yes | Number of units included: 1 pc(s) | Operating temperature (T-T): 0 - 40 °C | Processor frequency: 1.5 GHz | Package width: 241 mm | Security algorithms: WPA | Ethernet LAN (RJ-45) ports: 3

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950