



TP-Link LiteWave 8-Port Gigabit Desktop Switch with 8- Port PoE+



Model: LS108GP

Manufacturer: TP-LINK

EAN: 4895252505986

Product Code: 1111683

R1,574

Certification: CE, FCC, RoHS | Switching capacity: 16 Gbit/s | Heat dissipation: 243.47 BTU/h | Forwarding rate: 11.9 Mpps | Switch type: Unmanaged | Cable types supported: Cat3 | Cable types supported: Cat4 | Cable types supported: Cat5 | Cable types supported: Cat5e | Jumbo frames: 16000 | Power over Ethernet plus (PoE+) ports quantity: 8 | MAC address table: 4000 entries | Power supply included: Yes | Power connector: DC-in jack | Warnings: Do not open the case or try to repair it yourself. | Auto-negotiation: Yes | Warnings: Ensure the unit is adequately ventilated during operation. | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | DC input voltage: 53.5 V | 10G support: No | Flow control support: Yes | Input current: 1.31 A | Networking standards: IEEE 802.3i | Networking standards: IEEE 802.3at | Product colour: Black | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3ab | _____

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Networking standards: IEEE 802.1p | AC input voltage: 220 V | Networking standards: IEEE 802.3x | LED indicators: Yes | User guide: Yes | Power over Ethernet (PoE): Yes | Package type: Box | Operating relative humidity (H-H): 10 - 90% | Depth: 99 mm | Width: 158 mm | Networking standards: IEEE 802.3z | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.3u | Power over Ethernet (PoE) power per port: 30 W | Power consumption (max): 71.61 W | AC input frequency: 50 Hz | Height: 25 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Auto MDI/MDI-X: Yes | Operating temperature (T-T): 0 - 40 °C | Total Power over Ethernet (PoE) budget: 62 W | Power source: DC/PoE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950