



Switch UBIQUITI Pro Max 16 Type L3 USW-PRO- MAX-16



Model: USW-PRO-MAX-16

Manufacturer: UBIQUITI

EAN: 810084694565

Product Code: 1112537

R7,206

A 16-port, Layer 3 Etherlighting™ switch 2.5 GbE and versatile mounting options.

- Etherlighting™ ports that illuminate to indicate port location, speed/link, and native VLAN/network*
- (4) 2.5 GbE RJ45 ports
- (12) GbE RJ45 ports
- (2) 10G SFP+ ports
- Versatile desktop, wall, and rack** mounting
- Silent, fanless cooling system

Summary: Ubiquiti Pro Max 16. Switch layer: L3. Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500), Basic switching RJ-45 Ethernet ports quantity: 16. MAC address table: 16000 entries, Switching capacity: 84 Gbit/s. Networking standards: IEEE 802.1x. Power connector: AC/DC. Rack mounting, Form factor: 1U | Vendor Homepage: [ubiquiti.com](#)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](#) | [sales@cssi.co.za](#) | +27 (11)541-9950

<https://eu.store.ui.com/eu/en/pro/products/usw-pro-max-16> | Switch layer: L3 | Quality of Service (QoS) support: Yes | Basic switching RJ-45 Ethernet ports quantity: 16 | Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500) | Gigabit Ethernet (copper) ports quantity: 12 | 2.5G Ethernet (copper) ports quantity: 4 | SFP+ module slots quantity: 2 | Power connector: AC/DC | Networking standards: IEEE 802.1x | 10G support: Yes | Port mirroring: Yes | Broadcast storm control: Yes | Flow control support: Yes | IPv4 routes: 512 | Link aggregation: Yes | Rate limiting: Yes | VLAN support: Yes | Virtual LAN features: Voice VLAN | Number of VLANs: 1000 | Switching capacity: 84 | Throughput: 42 | Forwarding rate: 62 | MAC address table: 16000 | Static route: Yes | Jumbo frames support: Yes | Packet buffer memory: 1.5 | DHCP features: DHCP guarding/DHCP relay/DHCP server/DHCP snooping | Access Control List (ACL): Yes | IGMP snooping: Yes | Authentication type: IEEE 802.1x | Loop protection: Yes | Rack mounting: Yes | Stackable: Yes | Form factor: 1U | Product colour: Grey | Housing material: SGCC | Reset button: Yes | LED indicators: Link/Network/Speed/Status | Display type: LCM | Fanless: Yes | Power supply included: Yes | Redundant power supply (RPS) support: Yes | Input current: 5 | Input voltage: 4.8 - 5.2 | Power consumption (max): 25 | Power over Ethernet (PoE): No | Operating temperature (T-T): -5 - 40 | Operating relative humidity (H-H): 10 - 90 | Heat dissipation: 85.3 | Width: 325.1 | Depth: 160 | Height: 43.7 | Weight: 1950 | Cables included: Power | Rack mount kit: Yes | Compliance certificates: CE/Federal Communications Commission (FCC)/Industry Canada (IC)/National Defense Authorization Act (NDAA) | Unit Calculated Weight: 3.4625 | Product Net Weight: 1.95 | Unit Calculated Volume: 0.0167344 | Units per Shipping Box: 4 | Unit Width: 11 | Shipping Box Height: 25 | Unit Depth: 51 | Unit Height: 24.5 | Name: NET SWITCH 16PORT 2.5GBE/USW-PRO-MAX-16 UBIQUITI | Model: USW-Pro-Max-16 | Model name: Pro Max 16

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](mailto:sales@cssi.co.za) | sales@cssi.co.za | +27 (11)541-9950