



TP-Link Archer 4G+ Cat6 AC1200 Wireless Dual Band Gigabit Router



Model: Archer MR505

Manufacturer: TP-LINK

EAN: 8885020620078

Product Code: 1113477

R2,802

Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Warnings: Do not expose the device to water or moisture. | Warnings: Do not expose the device to extreme temperatures. | Ethernet LAN data rates: 10 | Quick start guide: Yes | DC-in jack: Yes | DHCP client: Yes | Ethernet LAN data rates: 1000 Mbit/s | Security algorithms: WPA3 | Product colour: White | Ethernet LAN data rates: 100 | Security algorithms: 128-bit WEP | Security algorithms: 64-bit WEP | Security algorithms: WPA | WLAN data transfer rate (max): 1200 Mbit/s | Storage relative humidity (H-H): 5 - 90% | Operating relative humidity (H-H): 10 - 90% | 3G standards: UMTS | Wi-Fi standards: 802.11g | Cabling technology: 10/100/1000Base-T(X) | Detachable antenna(s): Yes | Operating temperature (T-T): 0 - 40 °C | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Output voltage: 12 V | SIM card slot: Yes | Wi-Fi standards: 802.11b | Depth: 157.5 mm | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G standards: HSPA+ | Ethernet WAN: Yes | USB port: No | Output current: 1.5 A | Ethernet LAN: Yes | 3G standards: DC-HSPA+ | Antennas quantity: 2 | Wi-Fi

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

standards: Wi-Fi 4 (802.11n) | Wi-Fi standards: 802.11a | Height: 57 mm | Product type: Desktop/pole router | 4G standard: LTE-TDD & LTE-FDD | Ethernet LAN (RJ-45) ports: 3 | 4G bands supported: 2100 | 4G bands supported: 800 | 4G bands supported: 700 | 4G bands supported: 2300 | 4G bands supported: 2600 | 4G bands supported: 850 | 4G bands supported: 2500 MHz | DHCP server: Yes | AC adapter included: Yes | 4G bands supported: 1800 | Package type: Box | 4G bands supported: 900 | Ethernet LAN interface type: Gigabit Ethernet | Dynamic DNS (DDNS): Yes | Power source type: DC | Width: 212 mm | WLAN data transfer rate (second band): 867 Mbit/s | VPN server: Y | Static route: Yes | Mobile network generation: 4G | 3G bands supported: 850 | 3G bands supported: 900 MHz | 3G bands supported: 2100 | Indication light: Yes | Parental control: Yes | Antenna design: Internal | Number of guest networks (5 GHz): 1 | Number of guest networks (2.4 GHz): 1 | WLAN data transfer rate (first band): 300 Mbit/s

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950