



Tenda AC10 wireless router Gigabit Ethernet Dual-band (2.4 GHz 5 GHz) Black

Model: AC10

Manufacturer: TENDA

EAN: 6932849427547

Product Code: 1113531

R1,097

VPN support: PPTP Client, PPTP Server, L2TP Client | Certification: CE, FCC, RoHS, BSMI, NCC, EAC, IC
| Antenna design: External | 3G/4G USB modem compatibility: No | Cables included: LAN (RJ-45) |
Height: 70 mm | Product type: Tabletop router | Width: 198 mm | Wi-Fi standards: 802.11b | Wi-Fi
standards: 802.11g | Antennas quantity: 4 | Number of products included: 1 pc(s) | Firewall: Yes | Wi-
Fi standards: Wi-Fi 4 (802.11n) | WLAN data transfer rate (second band): 867 Mbit/s | Depth: 390 mm
| Package height: 70 mm | Port forwarding: Yes | WAN connection type: RJ-45 | Wi-Fi standards: Wi-Fi
5 (802.11ac) | Transmit power: 23 dBmW | Wi-Fi standards: 802.11a | Ethernet LAN interface type:
Gigabit Ethernet | Dynamic DNS (DDNS): Yes | WLAN data transfer rate (max): 867 Mbit/s | WPS push
button: Yes | Universal Plug and Play (UPnP): Yes | Output voltage: 12 V | Mac operating systems
supported: Yes | DSL WAN: No | Mac compatibility: Yes | Ethernet LAN: Yes | SIM card slot: No | On/off
switch: Yes | Indication light: Yes | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | DMZ support: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices
may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or
typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

System event log: Yes | USB port: No | Static route: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Harmonized System (HS) code: 85176990 | Cabling technology: 10/100/1000Base-T(X) | Ethernet WAN: Yes | Output current: 2 A | WLAN data transfer rate (first band): 300 Mbit/s | Ethernet LAN data rates: 1000 Mbit/s | Memory card slot(s): No | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | AC input frequency: 50 - 60 Hz | LED indicators: LAN, System, WAN, WLAN, WPS | Filtering: Yes | Package width: 198 mm | Package weight: 810 g | Windows operating systems supported: Windows XP | Antenna gain level (max): 5 dBi | Linux operating systems supported: Yes | AC input voltage: 100 - 240 V | Reset button: Yes | 4G: No | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 100 | Windows operating systems supported: Windows 10 | Windows operating systems supported: Windows 8 | DHCP server: Yes | Windows operating systems supported: Windows 7 | Package type: Box | Power source type: DC | Security algorithms: WPA2-PSK | Networking standards: IEEE 802.11b | Security algorithms: WPS | Security algorithms: WPA2 | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | MAC address filtering: Yes | Security algorithms: WPA | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.11a | DC-in jack: Yes | DHCP client: Yes | Operating temperature (T-T): 0 - 40 °C | 3G: No | Weight: 350 g | Ethernet LAN (RJ-45) ports: 3 | Quick installation guide: Yes | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.11ac | Product colour: Black | Package depth: 390 mm | Storage temperature (T-T): -40 - 70 °C | Operating relative humidity (H-H): 10 - 90% | AC adapter included: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950