



TP-Link Omada ES208GP network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) DIN rail Black

Model: ES208GP

Manufacturer: TP-LINK

EAN: 1210002609708

Product Code: 1115403

R1,902

10G support: No | Loop protection: Yes | LED indicators: Yes | Number of VLANs: 4000 | Depth: 100.7 mm | Virtual LAN features: Port-based VLAN | Jumbo frames support: Yes | Input current: 1.31 A | Link aggregation: Yes | Store-and-forward: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Broadcast storm control: Yes | Virtual LAN features: Tagged VLAN | Virtual LAN features: MTU VLAN | Operating temperature (T-T): 0 - 40 °C | Total Power over Ethernet (PoE) budget: 64 W | Operating relative humidity (H-H): 10 - 90% | Multicast support: Yes | Height:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

25.4 mm | Cables included: Power | Product colour: Black | Switch type: Managed | Rack mounting: Yes | Width: 158 mm | IGMP snooping: Yes | Flow control support: Yes | Networking standards: IEEE 802.3bt | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.3at | Web-based management: Yes | Networking standards: IEEE 802.3af | Power over Ethernet (PoE): Yes | VLAN support: Yes | Forwarding rate: 11.904 Mpps | Power over Ethernet plus (PoE+) ports quantity: 8 | Quick start guide: Yes | Power source: DC | Basic switching RJ-45 Ethernet ports quantity: 8 | Switching capacity: 16 Gbit/s | Ethernet LAN data rates: 10,100,1000 Mbit/s | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Port mirroring: Yes | Form factor: DIN rail | Auto MDI/MDI-X: Yes | Packet buffer memory: 0.5 MB | DHCP features: DHCP client | MAC address table: 8000 entries | Auto-negotiation: Yes | Switch layer: L2 | Cloud-managed: Yes | Power over Ethernet (PoE) type supported: PoE+ | Jumbo frames: 15000 | Transmission distance (max): 0.25 km | DC input voltage: 53 V | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: RoHS | Compliance certificates: CE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950