



Wireless Router DAHUA AC12 AC1200 Wireless Router Wi-Fi 5 (802.11ac) Data speed 1200 Mbit/s Ethernet WAN Yes WAN connection type RJ-45 Ethernet LAN Yes 4xLAN ports AC12

Model: AC12

Manufacturer: DAHUA

EAN: 6923172557315

Product Code: 1125964

R820 ~~R1,184~~

DH-AC12 Gigabit Wireless Router has a wide signal coverage and fast wireless speed. It complies with the IEEE 802.11ac standard, and its wireless speed reaches up to 1,167 Mbps, allowing smooth internet access. It uses beamforming technology to widen its Wi-Fi coverage, and has a built-in 1 GHz high-performance processor, which provides it with strong processing capabilities and high data transmission speeds. The router can be managed through the WiLynk app and provides wireless networks, making it a great choice for common wireless applications.

- 1.2 Gbps Wireless Speed(300 Mbps@2.4 GHz, 867 Mbps@5 GHz)
- Backward compatible (IEEE 802.11 b/g/n/ac standard)
- Beamforming for better Coverage
- Bi-directional MU-MIMO
- WiFi protected Access(WPA/WPA2)
- Guest Wi-Fi
- Parental Control

Summary: Dahua Technology AC12 AC1200 Wireless Router. WAN connection type: RJ-45. Wi-Fi band: Dual-band (2.4 GHz / 5 GHz), Top Wi-Fi standard: Wi-Fi 5 (802.11ac), WLAN data transfer rate (max): 1200 Mbit/s. Ethernet LAN interface type: Ethernet, Ethernet LAN data rates: 10,100,1000 Mbit/s, Cabling technology: 10/100/1000Base-T(X). Security algorithms: 64-bit WEP, 128-bit WEP, WEP, WPA, WPA2. Product type: Tabletop router, Product colour: Black | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Transmission/IT-Channel-Products/Wireless-Router/AC12> | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | WLAN data transfer rate (max): 1200 | Wi-Fi standards: 802.11a/802.11b/802.11g/Wi-Fi 4 (802.11n)/Wi-Fi 5 (802.11ac) | WLAN data transfer rate (first band): 300 | WLAN data transfer rate (second band): 867 | Channels quantity: 165 | Channel bandwidth: 80 | Ethernet WAN: Yes | DSL WAN: No | SIM card slot: No | 3G/4G USB modem compatibility: No | WAN connection type: RJ-45 | Ethernet LAN: Yes | Ethernet LAN interface type: Ethernet | Ethernet LAN data rates: 10/100/1000 | Cabling technology: 10/100/1000Base-T(X) | Networking standards: IEEE 802.11a/IEEE 802.11ac/IEEE 802.11b/IEEE 802.11g/IEEE 802.11n/IEEE 802.3/IEEE 802.3ab/IEEE 802.3u | Automatic channel selection: Yes | Dynamic DNS (DDNS): Yes | VPN Passthrough: Yes | Receiver sensitivity: 5GHz 11ac VHT80_MCS0: -89dbm 11ac VHT80_MCS9:-62dbm 2.4GHz 11n HT20_MCS0: -95dbm 11n HT20_MCS7: -75dbm 11n HT40_MCS0: -92dbm 11n HT40_MCS7: -72dbm | Ethernet LAN (RJ-45) ports: 4 | USB port: No | DC-in jack: Yes | Web-based management: Yes | Quality of Service (QoS) support: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

MIMO: Yes | MU-MIMO technology: Yes | Security algorithms: 128-bit WEP/64-bit WEP/WEP/WPA/WPA2 | Parental control: Yes | System event log: Yes | Network address translation (NAT): Yes | DHCP client: Yes | DHCP server: Yes | Product colour: Black | Wall mountable: Yes | Indication light: Yes | Product type: Tabletop router | Cables included: LAN (RJ-45) | AC adapter included: Yes | Manual: Yes | Quick start guide: Yes | Antenna design: External | Antenna gain level (max): 5 | Antennas quantity: 4 | Internal memory: 64 | Number of simultaneously connected devices (max): 32 | Firmware upgradeable: Yes | Power source type: DC | Output voltage: 12 | Output current: 1 | Power consumption (typical): 12 | External power adapter: Yes | Operating relative humidity (H-H): 0 - 90 | Operating temperature (T-T): 0 - 40 | Storage temperature (T-T): 20 - 70 | Depth: 222 | Height: 188.4 | Weight: 310 | Width: 147.4 | Package width: 260 | Package depth: 300 | Package height: 70 | Number of products included: 1 | Bandwidth (first): 2.484 | Bandwidth (second): 5.85 | Unit Calculated Weight: 0.61 | Product Net Weight: 0.31 | Unit Calculated Volume: 0.00546 | Units per Shipping Box: 1 | Unit Width: 7 | Shipping Box Height: 26 | Unit Depth: 30 | Unit Height: 26 | Name: WRL ROUTER 1200MBPS/AC12 DAHUA | Model name: AC12 AC1200 Wireless Router

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950