



Lenovo ThinkVision E65 LFD computer monitor 163.8 cm (64.5) 3840 x 2160 pixels 4K Ultra HD LCD Black

Model: 64ACGAT1EK

Manufacturer: LENOVO

EAN: 198156603623

Product Code: 1128055

R23,039

Certification: EU Energy Label (F-class) TÜV Rheinland® Flicker Free TÜV Rheinland® Low Blue Light (Hardware Solution) | European Product Registry for Energy Labelling (EPREL) code: 2262153 | DisplayPort out quantity: 1 | Number of USB Type-B upstream ports quantity: 1 | Backlight type: Direct LED | USB Type-A downstream ports quantity: 4 | Number of USB Type-C upstream ports quantity: 1 | Energy consumption (SDR) per 1000 hours: 100 kWh | Contrast ratio (typical): 5000:1 | Colour gamut: 72% | Bezel width (side): 1.9 mm | Energy efficiency class (HDR): G | Built-in KVM switch: Yes | RMS rated power: 10 W | Energy efficiency class (SDR): F | Maximum refresh rate: 60 Hz | Built-in speaker(s): Yes | Headphone connectivity: 3.5 mm | Number of speakers: 2 | Power supply

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

type: Internal | AMD FreeSync: No | USB upstream port type: USB Type-C | Built-in microphone: No | Panel mounting interface: 300 x 300 mm | Wi-Fi standards: Not supported | Power consumption (average): 110 W | Power consumption (max): 380 W | Audio output: Yes | Built-in camera: No | Depth: 126 mm | Picture-in-Picture: Yes | Number of upstream ports: 2 | Ethernet LAN: Yes | Display brightness: 400 cd/m² | Height (with stand): 847 mm | DisplayPort version: 1.4 | NVIDIA G-SYNC: No | Viewing angle, horizontal: 178° | Package weight: 31.4 kg | Power consumption (standby): 0.5 W | Viewing angle, vertical: 178° | Panel type: IPS | Bezel width (bottom): 2.12 cm | Ethernet LAN (RJ-45) ports: 1 | LED backlight: Yes | AC input frequency: 50/60 Hz | Package width: 1620 mm | Display number of colours: 1.07 billion colours | Power consumption (off): 0.5 W | Screen shape: Flat | Display brightness (typical): 400 cd/m² | Tilt adjustment: Yes | Native aspect ratio: 16:9 | Depth (with stand): 126 mm | Built-in USB hub: Yes | HD type: 4K Ultra HD | Display resolution: 3840 x 2160 pixels | Response time: 8 ms | Weight: 25.1 kg | HDMI version: 2.1 | RS-232 ports: 1 | Ethernet LAN data rates: 1000 Mbit/s | Pixel pitch: 0.372 x 0.372 mm | HDMI ports quantity: 2 | Width: 1446.3 mm | Height adjustment: No | Touchscreen: No | Package depth: 188 mm | AC input voltage: 100 - 240 V | Package height: 945 mm | Energy consumption (HDR) per 1000 hours: 220 kWh | Display technology: LCD | DisplayPorts quantity: 2 | Windows operating systems supported: Windows 11 | Windows operating systems supported: Windows 10 | Height: 847 mm | Wi-Fi: No | VESA mounting: Yes | Weight (with stand): 25.1 kg | Power consumption (typical): 110 W | Sustainability certificates: EPEAT Silver | Sustainability certificates: ENERGY STAR | Display surface: Matt | Width (with stand): 1446.3 mm | Product colour: Black | Bluetooth: No | Tilt angle range: 0.1 - 5° | Display diagonal: 163.8 cm (64.5") | Aspect ratio: 16:9 | Bezel width (top): 1.9 mm | Pixel density: 68 ppi | USB 2.0 Type-A ports quantity: 4 | USB Type-C DisplayPort Alternate Mode: Yes | sRGB coverage (typical): 95% | Anti-glare screen: Yes | NTSC coverage (typical): 72% | USB Power Delivery up to: 96 W | Energy efficiency scale: A to G | USB Power Delivery (USB PD): Yes | Colour depth: 10 bit | USB Type-C downstream ports quantity: 1 | High Dynamic Range (HDR) supported: Yes | Cable management: Yes | Colour name: Black | RJ-45 ports quantity: 1 | DCI-P3 coverage: 75% | High Dynamic Range (HDR) technology: High Dynamic Range 10 Pro (HDR10 Pro) | HDMI: Yes | Warnings: Unplug the monitor from the power source before cleaning. | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | DisplayPort out version: 1.4 | Compliance certificates: RoHS

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950