



Lenovo ThinkVision P24QD-40 Monitor

Model: 64B1GAT1EU

Manufacturer: LENOVO

EAN: 198156544872

Product Code: 1138736

R6,512

Certification: ENERGY STAR Certified, TCO 10.0, TCO Edge 2.1, EU Energy Efficiency Level (Level-D), EPEAT Gold TÜV Rheinland Eye Comfort 5 Stars, Eyesafe Display 2.0, TÜV Low Blue Light (Hardware solution) | Quick start guide: Yes | Cables included: DisplayPort | Windows operating systems supported: Windows 11 | Power consumption (max): 210 W | Viewing angle, vertical: 178° | LED backlight: Yes | Package type: Box | Depth (with stand): 190 mm | NVIDIA G-SYNC: No | Height (with stand): 505.8 mm | Native aspect ratio: 16:9 | Response time: 6 ms | DisplayPort version: 1.4 | Display diagonal: 60.5 cm (23.8") | Package weight: 8.4 kg | HDMI ports quantity: 1 | Cables included: USB Type-A to USB Type-B | Cables included: Power | Tilt adjustment: Yes | Display brightness (typical): 300 cd/m² | Operating relative humidity (H-H): 10 - 80% | Display resolution: 2560 x 1440 pixels | AC input frequency: 50/60 Hz | Windows operating systems supported: Windows 10 | Built-in USB hub: Yes | Panel mounting interface: 100 x 100 mm | Product colour: Black | Cable lock slot: Yes | Cable lock slot type: Kensington | Built-in microphone: No | Display number of colours: 16.7 million colours | Power consumption (off): 0.3 W | HD type: Quad HD | Viewing angle, horizontal: 178° | AC input voltage: 100 - 240 V | Tilt angle range: -5 - 23.5° | Touchscreen: No | Backlight type:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

W-LED | Ethernet LAN data rates: 2500 | Package height: 420 mm | HDMI version: 2.1 | Ethernet LAN: Yes | Screen shape: Flat | Operating temperature (T-T): 0 - 40 °C | Cables included: USB Type-C to USB Type-C | Contrast ratio (dynamic): 3000000:1 | DisplayPorts quantity: 2 | Power consumption (typical): 16.5 W | Pixel pitch: 0.2058 x 0.2058 mm | Package depth: 123 mm | Height adjustment: Yes | Storage temperature (T-T): -20 - 60 °C | Ethernet LAN (RJ-45) ports: 1 | Package width: 730 mm | Storage relative humidity (H-H): 5 - 95% | Power consumption (standby): 0.5 W | Power supply type: Internal | VESA mounting: Yes | Width (with stand): 539.8 mm | AMD FreeSync: No | Bezel width (top): 2 mm | Colour gamut: 99% | Maximum refresh rate: 120 Hz | USB upstream port type: USB Type-B | USB upstream port type: USB Type-C | Bezel width (side): 2 mm | USB Power Delivery (USB PD): Yes | Display diagonal (metric): 60.5 cm | Contrast ratio (typical): 1500:1 | USB Type-A downstream ports quantity: 4 | USB Power Delivery up to: 140 W | Anti-glare screen: Yes | USB Type-C DisplayPort Alternate Mode: Yes | Built-in KVM switch: Yes | Viewable size diagonal: 29.6 cm | Power cable length: 1.8 m | Panel type: IPS | Energy efficiency class (SDR): D | Pivot: Yes | Stand included: Yes | Energy efficiency scale: A to G | Built-in speaker(s): No | Headphone out: No | European Product Registry for Energy Labelling (EPREL) code: 2310433 | Height (without stand): 315.8 mm | Colour gamut standard: Rec. 709 | Pivot angle: -90 - 90° | Number of USB Type-C upstream ports quantity: 1 | Built-in camera: No | DisplayPort out version: 1.4 | DisplayPort out quantity: 1 | Energy consumption (SDR) per 1000 hours: 14 kWh | Swivel angle range: -45 - 45° | Weight (without stand): 3.6 kg | Energy efficiency class (HDR): F | Number of USB Type-B upstream ports quantity: 1 | Colour depth: 8 bit | Width (without stand): 539.8 mm | Plug and Play: Yes | Response time (fast): 4 ms | Depth (without stand): 45.3 mm | Front bezel colour: Black | Display technology: LCD | Number of upstream ports: 2 | Bezel width (bottom): 1.15 cm | Colour name: Eclipse Black | Low Blue Light technology: Yes | Detachable stand: Yes | DisplayPort cable length: 1.8 m | sRGB coverage (typical): 99% | Pixel density: 123 ppi | High Dynamic Range (HDR) technology: High Dynamic Range 10 (HDR10) | Feet colour: Black | High Dynamic Range (HDR) supported: Yes | Weight (with stand): 5.6 kg | Energy consumption (HDR) per 1000 hours: 22 kWh | Swivelling: Yes | USB Type-C downstream ports quantity: 1 | Viewable size, vertical: 52.7 cm | HDMI: Yes | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | Adjustable height (max): 15.5 cm | Warnings: Unplug the monitor from the power source before cleaning. | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | Response time measurement type: GTG (Gray to Gray)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950