



TP-Link Omada Pro S6500- 24GP4XF network switch Managed L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Grey



Model: S6500-24GP4XF

Manufacturer: TP-LINK

EAN: 4895252505511

Product Code: 1143463

R144,015

What This Product Does

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Omada Pro S6500-24GP4XF is a high-performance L3 managed PoE+ switch tailored for the access layer, featuring L3 routing, fast 10 Gbps wired speeds, stacking options, and redundant power supply modules. It boasts a 720 W PoE budget,*24× Gigabit RJ45 PoE+ ports, 4× 10 Gbps SFP+ slots, physical stacking ability, and centralized management. Integrated with strong security, easy O&A, and extensive management features, S6500-24GP4XF offers a dependable networking solution for SMBs, enterprises, and ISPs.

IEEE 802.3at/af-compliant Power over Ethernet

24× IEEE 802.3at/af-compliant PoE ports supply up to 720 W total power to 802.3at and 802.3af devices,* with each port supplying up to 30 W power. Set up wireless access points, surveillance cameras, IP phones, and other PoE devices quickly and easily, without the hassle and cost of installing power cabling. Perpetual PoE ensures an uninterrupted power supply to connected devices even during switch reboots. Additionally, the switch retains PoE power settings across reboots, thanks to fast PoE functionality.

High-speed Connectivity and Powerful Stacking

24× Gigabit RJ45 ports and 4× 10 Gbps SFP+ slots provide up to 128 Gbps switching capacity per unit. Physical stacking of up to 12 units△ enhances network performance and redundancy.

Abundant Layer 3 Capabilities

Comes with abundant Layer 3 routing protocols that support a scalable network, such as OSPF, BGP, IS-IS, VRRP, PIM-SM/PIM-DM/PIM-SSM, ECMP, and PBR. In complex large-scale network environments, dynamic routing protocols automatically adapt to changes in network topology and select the best transmission path based on real-time network conditions to maintain stability.

Comprehensive Security Functions

Defend against a range of network threats with MACsec, Secure Boot, RADSEC, IMPB, SFTP, and 802.1X. MACsec works with the 802.1X protocol to ensure secure communication of all traffic on Ethernet links. Secure Boot protects the operating system from malicious attacks.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Highly Available

Two field-replaceable redundant power supplies and VRRP make it an ideal choice for reliable networking architecture. ERPS supports rapid protection and recovery in a ring topology, while BFD enables sub-second failure detection for rapid routing protocol rebalancing.

Easy Operation and Maintenance

The switch can be configured and managed based on the NETCONF protocol, reducing manual configuration errors and improving software upgrade efficiency. Configuration Rollback restores previous settings if errors occur. Hot patching technology allows software defects to be fixed without device restart, preventing business interruptions.

Omada Pro Integration

Integration into the Omada Pro system brings centralized cloud management and a series of management features, such as Zero-Touch Provisioning (ZTP) and Intelligent Anomaly Detection.† Omada Pro's Software Defined Networking (SDN) platform integrates network devices, including access points, switches, and routers, providing 100% centralized cloud management. Omada Pro creates a highly scalable network—all controlled from a single interface.

Apart from central management via the web or Omada app, S6500-24GP4XF can be managed through an intuitive web GUI or industry-standard CLI, both secured with SSL or SSH encryption. SNMP (v1/v2c/v3) and RMON support provide status polling and abnormal event notifications.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950