



UBIQUITI USW-48-POE UniFi Managed Switch gen2 32x Gigabit POE+ ports 16x Gigabit POE ports 4x SFP 1GB Ports 32W per port

Model: USW-48-POE

Manufacturer: UBIQUITI NETWORKS

EAN: 817882029094

Product Code: 1176114

R15,577

The USW-48-PoE is a configurable Gigabit Layer 2 switch with 48 Gigabit Ethernet ports, including 32 auto-sensing 802.3at PoE+ ports and 4 SFP ports. It provides Gigabit PoE links to your RJ45 Ethernet devices and Gigabit fiber uplink options to your enterprise network. The USW-48-PoE features a 1.3" touch LCM to provide status.

Managed and configured by the UniFi Network Controller with UniFi mobile app support, the USW-48-

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

PoE offers an extensive suite of advanced Layer 2 switching protocols and features, including operation mode (switching, mirroring, or aggregate) per port. The UniFi Network Controller and mobile app allow admins to configure and monitor virtually all of the switch features in a graphical user interface from anywhere.

Product Description: Ubiquiti UniFi Switch USW-48-POE - switch - 48 ports - Managed - rack-mountable | Device Type: Switch - 48 ports - Managed | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 48 x 10/100/1000 (32 PoE+) + 4 x Gigabit SFP | Power Over Ethernet (PoE): PoE+ | PoE Budget: 195 W | Performance: Non-blocking bandwidth: 18 Gbps Switching capacity: 36 Gbps Forwarding rate: 26.78 Mpps | Features: 16KV ESD Protector (air-gap discharge), 12KV ESD Protector (contact discharge), fanless, GVRP, auto-uplink (auto MDI/MDI-X), port mirroring, aggregation mode, Jumbo Frames support, flow control, DPI, Storm Control, Layer 2 switching | Compliant Standards: IEEE 802.3af, IEEE 802.3at, IEEE 802.1x | Power: AC 120/230 V (50/60 Hz) | Dimensions (WxDxH): 44.24 cm x 28.5 cm x 4.37 cm | Weight: 4.52 kg | System Requirements: Linux, Apple MacOS, Microsoft Windows 7 / 8 / 10 | Manufacturer Warranty: 1-year warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950