

## **Ruijie Networks RG-ES200 Managed L2 Gigabit Ethernet (10/100/1000) Desktop/Wall- Mounting Black**



Model: RG-ES216GC-V2

Manufacturer: RUIJIE

EAN: 6971693278714

Product Code: 1177702

## **R4,021**

Packaging content: Warranty card Rubber pad x 4 Power cord retainer | Surge protection voltage: 4 kV | MAC address entries: Static MAC address entries | Fanless: Yes | Cloud-managed: Yes | Jumbo frames: 10000 | Warranty period: 3 year(s) | Product colour: Black | LED indicators: Yes | Power source: AC | Operating altitude: -500 - 5000 m | AC adapter included: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Number of VLANs: 16 | Wall mountable: Yes | Cables included: Power | MAC address table: 8000 entries | AC input frequency: 50/60 Hz | Depth: 440 mm | 10G support: No | Stackable: Yes | Port mirroring: Yes | AC input voltage: 100 - 240 V | Mounting brackets included: Yes | Input current: 0.6 A | Operating temperature (T-T): 0 - 50 °C | Switching capacity: 32 Gbit/s | Weight: 2 kg | Multicast support: Yes | Flow control support: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Networking standards: IEEE 802.1Q | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | DHCP features: DHCP client | Storage relative humidity (H-H): 5 - 95% | Housing material: Metal | Rack mounting: Yes | Power over Ethernet (PoE): No | Screws included: Yes | Form factor: Desktop/Wall-Mounting | DHCP features: DHCP snooping | Switch layer: L2 | Reset button: Yes | Remote administration: Yes | Basic switching RJ-45 Ethernet ports quantity: 16 | VLAN support: Yes | Package type: Box | Width: 165 mm | Package weight: 2.7 kg | Height: 44 mm | Power consumption (typical): 12 W | Forwarding rate: 23.81 Mpps | Loop protection: Yes | Mean time between failures (MTBF): 200000 h | Switch type: Managed | Power supply included: Yes | Jumbo frames support: Yes | Surge protection: Yes | Operating relative humidity (H-H): 10 - 90% | Manual: Yes | Broadcast storm control: Yes | Power saving mode (EEE): Yes | Compliance certificates: CE

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950