



Ruijie Networks RG-NIS2100 Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black, Stainless steel

Model: RG-NIS2100-4GT2SFP-HP

Manufacturer: RUIJIE

EAN: 6976915001491

Product Code: 1177703

R5,268

Certification: IEC/EN 61000-4-2 IEC/EN 61000-4-3 IEC/EN 61000-4-4 IEC/EN 61000-4-5 IEC/EN 61000-4-6 IEC/EN 61000-4-8 | Compliance certificates: Federal Communications Commission (FCC) | Cloud-managed: Yes | Power over Ethernet (PoE) type supported: PoE++ (4PPoE) | Power over Ethernet (PoE) type supported: PoE+ | Compliance certificates: CE | Ethernet Ring Protection Switching (ERPS): Yes | Warranty period: 5 year(s) | Power over Ethernet 4PPoE (PoE++) ports quantity: 1 | Power saving mode (EEE): Yes | Width: 50 mm | Reset button: Yes | Networking standards: IEEE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

802.1Q | System event log: Yes | Surge protection voltage: 6 kV | DHCP features: DHCP client | Rack mounting: Yes | Power supply location: Internal | DIN rail mounting: Yes | Operating temperature (T-T): -40 - 75 °C | Product colour: Stainless steel | 10G support: No | MAC address table: 8000 entries | DC voltage range: 46 - 57 V | Wall mountable: Yes | Power source: DC/PoE | Web-based management: Yes | Installed SFP modules quantity: 2 | Number of fans: 0 fan(s) | Gigabit Ethernet (copper) ports quantity: 4 | Jumbo frames support: Yes | Number of power supply units: 1 | Power over Ethernet (PoE): Yes | Operating altitude: -500 - 5000 m | Product colour: Black | Surge protection: Yes | Number of VLANs: 16 | Total Power over Ethernet (PoE) budget: 180 W | Mean time between failures (MTBF): 200000 h | Switch type: Managed | Housing material: Metal | Port mirroring: Yes | Jumbo frames: 10000 | Storage temperature (T-T): -40 - 85 °C | Quality of Service (QoS) support: Yes | Rack mount kit: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Storage relative humidity (H-H): 5 - 95% | Heat dissipation: 1067.04 BTU/h | Broadcast storm control: Yes | Depth: 155 mm | DHCP features: DHCP snooping | Switch layer: L2 | Package weight: 1.08 kg | Height: 30 mm | Weight: 770 g | Power over Ethernet plus (PoE+) ports quantity: 4 | Power consumption (max): 192 W | Forwarding rate: 8.9 Mpps | Power over Ethernet (PoE) ports quantity: 4 | Operating relative humidity (H-H): 10 - 90% | Power supply included: Yes | Manual: Yes | Switching capacity: 12 Gbit/s | VLAN support: Yes | Basic switching RJ-45 Ethernet ports quantity: 4

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950