



TP-LINK 4G+ Cat6 AC1200 Wireless Dual Band Gigabit Router

Model: Archer MR600

Manufacturer: TP-LINK

EAN: 1210002615266

Product Code: 1178536

R3,393

VPN support: PPTP VPN, OpenVPN | Receiver sensitivity: 5 GHz: 11a 54M: -77 dBm 11ac HT20: -73 dBm 11ac HT40: -68 dBm 11ac HT80 : -64 dBm 11n HT20: -77 dBm 11n HT40: -73 dBm 2,4 GHz: 11g 54M: -74 dBm 11n HT20: -72 dBm 11n HT40: -69 dBm | Detachable antenna(s): Yes | 4G bands supported: 900 | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G standards: HSPA+ | Supported network protocols: IPv4, IPv6 | 3G standards: HSPA | DHCP server: Yes | 4G bands supported: 2100 | 4G bands supported: 800 | 4G bands supported: 1800 | 4G bands supported: 2600 | 4G bands supported: 850 | 4G bands supported: 2500 MHz | WAN connection type: RJ-45 | 3G standards: UMTS | Output current: 1.5 A | SIM card slot: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | Universal Plug and Play (UPnP): Yes | Memory card slot(s): Yes | 4G standard: LTE-TDD & LTE-FDD | SIM card type: NanoSIM | Firewall: Yes | 3G bands supported: 2100 | 4G bands supported: 700 | 4G bands supported: 2300 | 3G bands supported: 850 | Product type: Tabletop router | 3G bands supported: 900 | WLAN data transfer rate (first band): 867 Mbit/s | Parental control: Yes | Height: 33.6 mm | DMZ

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

support: Yes | WPS push button: Yes | 3G/4G USB modem compatibility: Yes | WLAN data transfer rate (second band): 300 Mbit/s | DoS attack prevention: Yes | Dynamic DNS (DDNS): Yes | Guest access: Yes | Number of guest networks (2.4 GHz): 1 | Number of guest networks (5 GHz): 1 | Antenna design: External | Ethernet LAN data rates: 100 | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Security algorithms: WPA2-PSK | Cables included: LAN (RJ-45) | WLAN data transfer rate (max): 867 Mbit/s | Stateful Packet Inspection (SPI): Yes | Product colour: Black | Quick installation guide: Yes | Networking standards: IEEE 802.11a | Reset button: Yes | Wi-Fi standards: 802.11g | Antennas quantity: 2 | Ethernet LAN data rates: 1000 Mbit/s | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | AC input frequency: 50 - 60 Hz | DHCP client: Yes | Security algorithms: WPA | Operating temperature (T-T): 0 - 40 °C | Operating relative humidity (H-H): 10 - 90% | Networking standards: IEEE 802.11b | Security algorithms: 128-bit WEP | Ethernet WAN: Yes | Width: 202 mm | Wi-Fi standards: 802.11a | AC adapter included: Yes | Ethernet LAN data rates: 10 | Networking standards: IEEE 802.11ac | AC input voltage: 110 - 240 V | Wi-Fi standards: 802.11b | Ethernet LAN interface type: Gigabit Ethernet | Wi-Fi standards: Wi-Fi 4 (802.11n) | Ethernet LAN (RJ-45) ports: 4 | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Output voltage: 12 V | Ethernet LAN: Yes | Depth: 141 mm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950