

 **TELTONIKA** | Networks

TRB142



**Teltonika
TRB142003000
Gateway,
2G/3G/4G LTE
(Cat 1),
Equipped with
RS232 for serial
communication
Teltonika LTE
Gateway
TRB142 No Wi-Fi
Mesh Support
No MU-MIMO No
2G/3G/4G
Antenna type 1
x SMA for LTE 1
x Virtual
network
interface via
micro USB**

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Model: TRB142003000
Manufacturer: TELTONIKA
EAN: 4779027312385
Product Code: 1180016

R3,617

Gross depth (mm): 175 | Gross height (mm): 71 | Gross weight: 0.391 | Gross width (mm): 149 | Net weight: 0.249 | Packing quantity: 1.00 | Tare weight (kg): 0.142 | Volume (m3): 0.001851325 | Embedded battery: No | WEEE tax: Yes | WEE classification: CL109:6:2017-04-01 | Paper/Pasteboard: 142 | USB ports quantity: 1 x Virtual network interface via micro USB | Producer product name: TRB142 | Producer product family: LTE Gateway | Ethernet LAN (RJ-45) ports: 0 | Wi-Fi band: No Wi-Fi | Software type: RutOS (OpenWrt based Linux OS) | Mesh Support: No | Mobile Broadband: 2G/3G/4G | MU-MIMO: No | Antenna type: 1 x SMA for LTE | Antennas quantity: 1 | Supported network protocols: TCP, UDP, IPv4, IPv6, ICMP, NTP, DNS, HTTP, HTTPS, SMTP, SSL v3, TLS, PPP, SSH, DHCP, SNMP, MQTT | Firewall security: Pre-configured firewall rules can be enabled via the WebUI, unlimited firewall configuration via CLI; NAT; NAT-T | Supported protocols: HTTP(S), MQTT, Azure MQTT, Kinesis | Processor model: ARM Cortex-A7 1.2 GHz CPU | Internal memory: 128 MB (50 MB available for userspace) | Other features: RS232 port | Input voltage: 9 – 30 VDC (4 pin industrial socket), reverse polarity protection, surge protection >33 VDC 10us max | LED indicators: 3 x connection type status LEDs, 5 x connection strength LEDs, 1x Power LED | Housing material: Aluminum | Dimensions (WxDxH): 74.5x64.4x25 | Producer: Teltonika | Palette Qty: 467 | Warranty: 24

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950