

 **TELTONIKA** | Networks

TRB140



**Teltonika LTE
Router TRB140
No Wi-Fi
10/100/1000
Mbit/s Mesh
Support No MU-
MIMO No
2G/3G/4G
Antenna type 1
x SMA for LTE 1
x Virtual
network
interface via
micro USB 24
month(s)**



Model: TRB140003000

Manufacturer: TELTONIKA

EAN: 4779027312408

Product Code: 1180020

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

R3,989

Gross depth (mm): 175 | Gross height (mm): 150 | Gross weight: 0.43 | Gross width (mm): 70.00 | Net weight: 0.307 | Packing quantity: 10 | Paper/Pasteboard: 123 | Tare weight (kg): 0.123 | Volume (m3): 0.0018375 | Embeeded battery: No | WEEE tax: Yes | WEE classification: CL109:6:2017-04-01 | Ethernet LAN data rates: 10/100/1000 | USB ports quantity: 1 x Virtual network interface via micro USB | Producer product name: TRB140 | Producer product family: LTE Router | Ethernet LAN (RJ-45) ports: 1 | Wi-Fi band: No Wi-Fi | Software type: RutOS (OpenWrt based Linux OS) | Mesh Support: No | Mobile Broadband: 2G/3G/4G | MU-MIMO: No | Antenna type: 1 x SMA for LTE | Processor model: ARM Cortex-A7 1.2 GHz CPU | SFP+ ports quantity: 0 | Warranty: 24 | Internal memory: 128 MB (50 MB available for userspace) | Housing material: Aluminum | Operating relative humidity (H-H): 10 % to 90 % non-condensing | Dimensions (WxDxH): 74,5x64,4x25 | Operating temperature (T-T): -40 °C to 75 °C | PoE in: Passive PoE over spare pairs. Possibility to power up through LAN port, not compatible with IEEE802.3af, 802.3at and 802.3bt standards | Input voltage: 9 – 30 VDC (4 pin industrial socket), reverse polarity protection, surge protection >33 VDC 10us max | Supported protocols: HTTP(S), MQTT, Azure MQTT, Kinesis | Firewall security: Pre-configured firewall rules can be enabled via the WebUI, unlimited firewall configuration via CLI; NAT; NAT-T | Supported network protocols: TCP, UDP, IPv4, IPv6, ICMP, NTP, DNS, HTTP, HTTPS, SMTP, SSL v3, TLS, PPP, PPPoE, SSH, DHCP, SNMP, MQTT, Wake on LAN (WOL) | Gross depth master carton: 375 | Gross width master carton: 370 | Gross height master carton: 170 | Net weight master carton: 4.3 | Tare weight master carton: 0.401 | Producer: Teltonika | Palette Qty: 730

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950