

 **TELTONIKA** | Networks

TRB145



**LTE Gateway: No
WiFi, 4G, SIM,
R485 port, Micro
USB Teltonika
LTE Gateway
TRB145 No Wi-Fi
Mesh Support
No MU-MIMO No
2G/3G/4G
Antenna type 1
x SMA for LTE 1
x Virtual
network
interface via
micro USB**

Model: TRB145003000

Manufacturer: TELTONIKA

EAN: 4779027312415

Product Code: 1180022

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

R3,617

Gross depth (mm): 170 | Gross height (mm): 150 | Gross weight: 0.388 | Gross width (mm): 70.00 | Net weight: 0.277 | Packing quantity: 1.00 | Paper/Pasteboard: 111 | Tare weight (kg): 0.111 | Volume (m3): 0.001785 | Embeeded battery: No | WEEE tax: Yes | WEE classification: CL109:6:2017-04-01 | USB ports quantity: 1 x Virtual network interface via micro USB | Antenna type: 1 x SMA for LTE | Producer product name: TRB145 | Producer product family: LTE Gateway | Ethernet LAN (RJ-45) ports: 0 | Wi-Fi band: No Wi-Fi | Software type: RutOS (OpenWrt based Linux OS) | Mesh Support: No | Mobile Broadband: 2G/3G/4G | MU-MIMO: No | Antennas quantity: 1 | Housing material: Aluminum | Dimensions (WxDxH): 74,5x64,4x25 | Operating relative humidity (H-H): 10 % to 90 % non-condensing | Operating temperature (T-T): -40 °C to 75 °C | Supported network protocols: TCP, UDP, IPv4, IPv6, ICMP, NTP, DNS, HTTP, HTTPS, SMTP, SSL v3, TLS, PPP, SSH, DHCP, SNMP, MQTT | Firewall security: Pre-configured firewall rules can be enabled via the WebUI, unlimited firewall configuration via CLI; NAT; NAT-T | Supported protocols: HTTP(S), MQTT, Azure MQTT, Kinesis | Internal memory: 128 MB (50 MB available for userspace) | Processor model: ARM Cortex-A7 1.2 GHz CPU | Voltage: 9 – 30 VDC (4 pin industrial socket), reverse polarity protection, surge protection >33 VDC 10us max | Other features: RS485 port | LED indicators: 3 x connection type status LEDs, 5 x connection strength LEDs, 1x Power LED | Producer: Teltonika | Palette Qty: 968 | Warranty: 24

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950