CSSi SA - "Securing Tomorrow, Today"
Waterfall Office Park, 28 Augrabies Rd Vorna Valley, Midrand, 1685
Generated: 2026-10-30 13:06

TP-Link 5-Port Gigabit Desktop PoE Switch with 4-Port

Model: TL-SG1005P

Manufacturer: TP-LINK

EAN: 1210002616607

Product Code: 1180704

R1,534

Certification: FCC, CE, RoHS | Storage relative humidity (H-H): 5 - 90% | Width: 99.8 mm | Rack mounting: No | MAC address table: 2000 entries | Auto MDI/MDI-X: Yes | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3u | Package width: 131 mm | Power over Ethernet (PoE) ports quantity: 4 | Power supply included: Yes | Copper ethernet cabling technology: 10BASE-T | Operating temperature (T-T): 0 - 40 °C | AC adapter included: Yes | Package depth: 196 mm | Product colour: Black | 10G support: No | LED indicators: Yes | Depth: 98 mm | Stackable: No | Manual: Yes | IGMP snooping: Yes | MAC address auto-aging supported: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | VLAN support: Yes | Copper ethernet cabling technology: 100BASE-TX | Package type: Box | Package height: 121 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | User guide: Yes | Power over Ethernet (PoE): Yes | Quick start guide: Yes | Forwarding rate: 7.44 Mpps | Total Power over Ethernet (PoE) budget: 56 W | DC input voltage: 48 V | Store-and-forward: Yes | Height: 25 mm | Heat dissipation: 219.87 BTU/h | Package weight: 761 g | Basic switching RJ-45 Ethernet ports quantity: 5 | Copper ethernet cabling technology: 1000BASE-T | MAC address auto-learning supported: Yes | Switch type: Unmanaged |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Power consumption (max): 64.44 W | Auto-negotiation: Yes | AC input voltage: 100 - 220 V | Operating relative humidity (H-H): 10 - 90% | Switching capacity: 10 Gbit/s | Power source: DC/PoE | Maximum cable length: 100 m | Input current: 1.25 A | Cable types supported: Cat3 | AC input frequency: 50 Hz | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3af | Harmonized System (HS) code: 85176990 | Flow control support: Yes | Cable types supported: Cat5 | Cable types supported: Cat5e | Cable types supported: Cat4 | Gigabit Ethernet (copper) ports quantity: 5 | Cables included: AC | Fanless: Yes | Sustainability compliance: Yes | Cable types supported: Cat6 | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: RoHS | Compliance certificates: CE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950