

**HP Series 3 Pro
27 inch FHD
Monitor - 327pf
computer
monitor 68.6 cm
(27") 1920 x
1080 pixels Full
HD LCD Black**



Model: B0CG3UT

Manufacturer: HEWLETT-PACKARD

EAN: 198828043597

Product Code: 1180771

R3,361

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Certification: Australia MEPS Bauart CCC CE CEL C-Tick cTUVus EAC E-standby (Korea) EUP Lot-5 EUP Lot-6 FCC ISO 9241-307 KC (Korean) requirements KCC (Korean) requirements NOM (Mexico) PSB for Singapore RCM SEPA S-Mark for Argentina Taiwan BSMI VCCI Vietnam MEPS Ukraine Energy label California Energy Commission (CEC) South Africa Energy EUP Lot 26 Mexico Energy UAE TGM India BIS Cambodia ISC IC NRCS PSE Ukraine CoC Ukraine DOC CEL Grade 2 CB(62368-1) CB 60950 | Manufacturer warranty: HP three-year limited warranty | Bundled software: HP Display Center HP Client Management Script Library | Energy efficiency class (HDR): Not available | Display diagonal (metric): 68.6 cm | Carbon emissions, manufacturing (kg of CO2e): 81 | Carbon emissions, end-of-life (kg of CO2e): 11 | European Product Registry for Energy Labelling (EPREL) code: 2207318 | Contrast ratio (typical): 1000:1 | Built-in speaker(s): No | Built-in camera: No | Power consumption (standby): 0.5 W | Total carbon emissions, w/o use phase (kg of CO2e): 30 | Display technology: LCD | Viewable size, vertical: 33.6 cm | Non-operating altitude: 0 - 12192 m | Panel type: IPS | Market positioning: Business | AMD FreeSync: No | Backlight type: Edge LED | Viewable size, horizontal: 59.8 cm | Power supply type: Internal | Width (without stand): 611 mm | Display brightness: 250 cd/m² | Weight (with stand): 5.05 kg | Colour name: Black | UNSPSC-code: 43211902 | Colour gamut: 72% | Headphone out: No | Maximum refresh rate: 100 Hz | NTSC coverage (typical): 72% | Energy efficiency scale: A to G | Depth (without stand): 57.1 mm | Haze rate: 25% | Anti-glare screen: Yes | Weight (without stand): 5.05 kg | HP segment: Business | Surface hardness: 3H | Colour depth: 8 bit | Detachable stand: Yes | Non-operating relative humidity (non-condensing): 20 - 80% | Height (without stand): 365.5 mm | Warranty card: Yes | Carbon emissions, logistics (kg of CO2e): 3 | Low Blue Light technology: Yes | HDMI: Yes | Sustainability compliance: Yes | Colour gamut standard: NTSC | Low halogen: Yes | Flicker-free technology: Yes | Sustainability certificates: ENERGY STAR | Sustainability certificates: TCO | Sustainability certificates: EPEAT | Sustainability certificates: TCO10 | Sustainability certificates: EPEAT Climate + | Energy efficiency class (SDR): D | Pixel density: 82 ppi | Energy consumption (SDR) per 1000 hours: 16 kWh | Feet colour: Black | Total carbon footprint (kg of CO2e): 130 | AC input voltage: 100 - 240 V | Height (with stand): 438.4 mm | Cable lock slot: Yes | Depth (with stand): 190.3 mm | Display surface: Matt | Power consumption (off): 0.3 W | Native aspect ratio: 16:9 | Horizontal scan range: 30 - 115 kHz | DisplayPorts quantity: 1 | Operating temperature (T-T): 5 - 35 °C | LED backlight: Yes | Tilt adjustment: Yes | DisplayPort version: 1.2 | Weight: 4.43 kg | Display diagonal: 68.6 cm (27") | Package height: 425 mm | Screen shape: Flat | Aspect ratio: 16:9 | Cables included: HDMI | HD type: Full HD | Display brightness (typical): 250 cd/m² | HDCP: Yes | Width (with stand): 611 mm | Response time: 5 ms | Tilt angle range: -5 - 20° | Power consumption (max): 35 W | Product colour: Black | Package depth: 137 mm | Quick start guide: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Operating relative humidity (H-H): 5 - 95% | VGA (D-Sub) ports quantity: 1 | Operating altitude: 0 - 5000 m | Power consumption (typical): 25 W | Pixel pitch: 0.3114 x 0.3114 mm | Supported graphics resolutions: 640 x 480 (VGA) | HDMI version: 1.4 | Vertical scan range: 48 - 100 Hz | Display resolution: 1920 x 1080 pixels | AC input frequency: 50/60 Hz | Package type: Box | Panel mounting interface: 100 x 100 mm | Supported graphics resolutions: 1680 x 1050 (WSXGA+) | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 800 x 600 (SVGA) | Supported graphics resolutions: 1280 x 1024 (SXGA) | On Screen Display (OSD): Yes | Viewing angle, horizontal: 178° | HDMI ports quantity: 1 | Supported graphics resolutions: 1280 x 800 | Supported graphics resolutions: 1600 x 900 | Package width: 685 mm | Viewing angle, vertical: 178° | Contrast ratio (dynamic): 8000000:1 | Built-in USB hub: No | Touchscreen: No | NVIDIA G-SYNC: No | Cables included: AC | Package weight: 7.65 kg | Display number of colours: 16.7 million colours | Supported graphics resolutions: 1024 x 768 (XGA) | Supported graphics resolutions: 1440 x 900 (WXGA+) | Height adjustment: No | Supported graphics resolutions: 720 x 400 | Storage relative humidity (H-H): 20 - 80% | Supported graphics resolutions: 1280 x 720 (HD 720) | VESA mounting: Yes | General Product Safety Regulation (GPSR) URL: <https://support.hp.com/gb-en/product/setup-user-guides/hp-color-laser-150-printer-series/model/24494355?sku=4ZB95A> <http://h10032.www1.hp.com/ctg/Manual/c06274333.pdf> <http://h10032.www1.hp.com/ctg/> | Compliance certificates: CCC | Compliance certificates: Federal Communications Commission (FCC) | Response time measurement type: GTG (Gray to Gray) | Compliance certificates: CE | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | Warnings: Unplug the monitor from the power source before cleaning. | Compliance certificates: BIS | Compliance certificates: BSMI | Compliance certificates: CB | Compliance certificates: EAC | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](mailto:sales@cssi.co.za) | sales@cssi.co.za | +27 (11)541-9950