

PLANET IGS-20160HPT network switch Managed L2/L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Blue, White

Model: IGS-20160HPT

Manufacturer: PLANET

EAN: 4711605281751

Product Code: 1181213

R20,165

Certification: FCC 15 A, CE | Weight: 1.55 kg | Number of trunks: 4 | Jumbo frames: 10000 | Virtual LAN features: Port-based VLAN | Installed SFP modules quantity: 2 | Multicast support: Yes | Virtual LAN features: Protocol-based VLAN | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.3ah | Housing material: Aluminium | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Security algorithms: SNMP | LED indicators: PoE | Switch type: Managed | LED indicators: Ring | Security algorithms: 128-bit SSL | Networking standards: IEEE 802.1D |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Networking standards: IEEE 802.3z | Storage relative humidity (H-H): 5 - 95% | Networking standards: IEEE 802.1ab | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Maximum data transfer rate: 1000 Mbit/s | Power over Ethernet (PoE): Yes | Total Power over Ethernet (PoE) budget: 320 W | DC input voltage: 48 - 56 V | DIN rail mounting: Yes | VLAN support: Yes | Wall mountable: Yes | Basic switching RJ-45 Ethernet ports quantity: 18 | Copper ethernet cabling technology: 1000BASE-T | Operating relative humidity (H-H): 5 - 95% | Storage temperature (T-T): -40 - 85 °C | Quality of Service (QoS) support: Yes | Number of VLANs: 255 | Virtual LAN features: Stacked VLAN | Number of multicast groups filtered: 255 | Virtual LAN features: Tagged VLAN | International Protection (IP) code: IP30 | Switching capacity: 46 Gbit/s | LED indicators: Power fail | Operating temperature (T-T): -40 - 75 °C | MAC address table: 32000 entries | Heat dissipation: 123 BTU/h | Rack mounting: No | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | LED indicators: Power | Multicast MAC address table: 4094 entries | MIB support: RFC-1213, IF, RFC-1493, RFC-1643, RFC-2863, RFC-2665, RFC-2819, RFC-2737, RFC-2618, RFC-2933, RFC-3411, LLDP, MAU | IGMP snooping: Yes | Auto-negotiation: Yes | 10G support: No | Networking standards: IEEE 802.3u | Packet buffer memory: 4 MB | Power over Ethernet (PoE) voltage range: 48 - 56 V | Networking standards: IEEE 802.1w | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-T | IP address table: 8 | Product colour: White | Routing entries: 32 | Fiber ethernet cabling technology: 1000BASE-LX | IP routing: Yes | Networking standards: IEEE 802.1x | Jumbo frames support: Yes | Full duplex: Yes | Fiber ethernet cabling technology: 1000BASE-SX | Safety: IEC60068-2-32, IEC60068-2-27, IEC60068-2-6 | Height: 152 mm | Reset button: Yes | Switch layer: L2/L3 | Port mirroring: Yes | Networking standards: IEEE 802.3af | LED indicators: Link | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Security algorithms: SSH | LED indicators: Activity | Access Control List (ACL): Yes | Width: 86 mm | Harmonized System (HS) code: 85176990 | Power over Ethernet (PoE) ports quantity: 16 | Link aggregation: Yes | Terminal block port: Yes | Throughput: 34.2 Mpps | Depth: 107 mm | Virtual LAN features: Private VLAN | Flow control support: Yes | Networking standards: IEEE 802.1ad | Store-and-forward: Yes | Product colour: Blue | Fiber ethernet cabling technology: 1000BASE-BX

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950