PLANET GS-5220-16S8CR network switch Managed L2+ Gigabit Ethernet (10/100/1000) 1U Blue

Model: GS-5220-16S8CR

Manufacturer: PLANET

EAN: 4711605280334

Product Code: 1181215

R12,400

Certification: FCC Part 15 Class A, CE | Reset button: Yes | Form factor: 1U | Virtual LAN features: Private VLAN | Operating temperature (T-T): 0 - 50 °C | Virtual LAN features: Voice VLAN | Console port: RS-232 | DHCP features: DHCP snooping | Store-and-forward: Yes | AC input frequency: 50 - 60 Hz | Product colour: Blue | Web-based management: Yes | MAC address filtering: Yes | DC input voltage: 36 - 72 V | Jumbo frames support: Yes | Access Control List (ACL): Yes | Link aggregation: Yes | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.1w | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Packet buffer memory: 16 MB | Cloud-managed:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Yes | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-T | Basic switching RJ-45 Ethernet ports quantity: 8 | SSH/SSL support: Yes | Number of static routes: 128 | BPDU filtering/protection: Yes | Throughput: 95.23 Mpps | Power over Ethernet (PoE): No | Width: 440 mm | Depth: 260 mm | Operating relative humidity (H-H): 5 - 95% | Input current: 0.6 A | Power consumption (typical): 36.2 W | Spanning tree protocol: Yes | Jumbo frames: 10000 | 10G support: No | LED indicators: Yes | Rack mounting: Yes | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Storage relative humidity (H-H): 5 - 95% | Switch type: Managed | Networking standards: IEEE 802.1ab | Security algorithms: SSL/TLS | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Virtual LAN features: Protocol-based VLAN | Installed SFP modules quantity: 24 | DHCP features: DHCP relay | MAC address table: 16000 entries | Quality of Service (QoS) support: Yes | Number of VLANs: 4094 | Authentication: MAC-based authentication, Port-based authentication | Number of multicast groups filtered: 255 | Fiber ports quantity: 24 | Height: 44 mm | Auto MDI/MDI-X: Yes | Switching capacity: 128 Gbit/s | IGMP snooping: Yes | Stackable: No | Virtual LAN features: Tagged VLAN | Weight: 3.5 kg | Multicast support: Yes | Virtual LAN features: Multicast VLAN | Housing material: Metal | Security algorithms: SNMPv3 | AC input voltage: 100 - 240 V | Ethernet LAN data rates: 10,100,1000 Mbit/s | Copper ethernet cabling technology: 1000BASE-T | Auto-negotiation: Yes | Loop protection: Yes | Networking standards: IEEE 802.1x | Heat dissipation: 102.9 BTU/h | Port mirroring: Yes | Harmonized System (HS) code: 85176990 | Fiber optic connector: SFP | VLAN support: Yes | Authentication type: RADIUS, TACACS+ | Power supply included: Yes | Queue scheduling algorithms: SP | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Full duplex: Yes | Traffic classification: Yes | Fiber ethernet cabling technology: 1000BASE-X | Fiber ethernet cabling technology: 100BASE-X | Switch layer: L2+ | Redundant power supply (RPS) support: Yes | Installed SFP+ modules quantity: 4 | Virtual LAN features: IP subnet–based VLAN | Security algorithms: SSH | Virtual LAN features: MAC address-based VLAN | System event log: Yes | Static route: Yes | ARP inspection: Yes | Storage temperature (T-T): -10 - 70 °C | Half duplex: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950