



D-Link DXS-3130-32S Managed L2/L3 1U Silver



Model: DXS-3130-32S/E

Manufacturer: D-LINK

EAN: 790069476952

Product Code: 1181491

R60,566

Versatile Traffic Management

Optimizes critical services with QoS, traffic shaping, multicast support, and ISM VLAN for enhanced efficiency

Simplified Management

The SIM feature enables managing multiple switches as a virtual stack with a single IP, supporting diverse management tools

Boosted Network Reliability

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

AC or DC RPS options ensure uninterrupted operation and boost switch reliability by preventing power disruptions

Advanced Security for Access

Supports authentication mechanisms such as 802.1X, Web/MAC-based access control for the easy deployment

High Availability and Scalability

Stack up to 9 switches with 200 Gbps bandwidth and unified IP for simplified control, fast failover and solid redundancy

Efficient Layer 3 Routing

Enables Layer 3 routing between different parts of your network, improving efficiency by directing traffic to its optimal destination

High-Speed Versatile Switching

Featuring flexible combinations of 10G SFP+ and 10GBase-T downlink ports + 4×10/25G SFP28 uplinks, this switch delivers flexible, high-performance connectivity. The 100M-10G auto-sensing ports optimize speed while 25G-capable uplinks handle heavy traffic. The full optical interface design optimizes speed and handles heavy traffic.

Perfect as a core switch for SMBs, enterprise aggregation, or Metro Ethernet edge, it combines rich software features with robust security for diverse deployments.

Unified the Power, Stack for Success

Scale your network with the DXS-3130 series by stacking up to 9 switches into a single physical or virtual unit. This simplifies management, improves redundancy, and allows control of the entire stack through one IP address. With up to 200 Gbps, physical stacking boosts capacity to meet growing network demands.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Built for Unbreakable Networks

The DXS-3130-32S ensures continuous uptime with redundant power and stacking. Its 50ms ERPS recovery minimizes downtime, loopback detection blocks storm-affected ports, and VRRP provides seamless backup routing making it ideal for hospitals, factories, and other mission-critical networks.

Optimized Performance for Critical Services

The DXS-3130-32S switch prioritizes mission-critical traffic like VoIP and IPTV through advanced QoS/CoS, traffic shaping, and L2 Multicast (IGMP/MLD Snooping). ISM VLAN further enhances bandwidth efficiency and security for multicast streaming.

Advanced QoS/CoS

Prioritizes critical traffic like VoIP and video, ensuring smooth performance and minimal latency for time-sensitive applications

IGMP/MLD Snooping

Multicast traffic streams only to intended recipients, reducing unnecessary bandwidth usage and enhancing network efficiency

ISM VLAN

Controls multicast across VLANs to reduce traffic and enhance security and performance on the large-scale network

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950