Switch DAHUA S3226-24ET-375

Switch type Unmanaged

Rack mounting Yes

24xRJ-45 ports RJ-45

Ports Type Fast Ethernet (10/100)

24xFast Ethernet (copper) ports quantity

2xCombo SFP ports quantity

Power over Ethernet (PoE) Yes

24xPower over Ethernet

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

(PoE) ports quantity 2xPower over Ethernet 4PPoE (PoE++) ports quantity Total Power over Ethernet (PoE) budget 375 W S3226-24ET-375

Model: S3226-24ET-375

Manufacturer: DAHUA

EAN: 6923172530561

Product Code: 1182920

R5,150

The PoE Switch is an unmanaged switch with a high-performance switch engine and large cache. It provides smooth transmission of video streams. It has 4 DIP switches and supports PoE watchdog, long distance PoE, VIP port and port isolation. The red port supports the IEEE802.3bt and the Hi-PoE standards and generates up to 90W. It can operate in temperatures ranging -10°C to 55°C. It offers EMC and has protection against overvoltage, overcurrent, static electricity, lightning strikes, pulses and other types of interference.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

BT 90W (Red Port)

The red ports support IEEE802.3af, IEEE802.3at, IEEE802.3bt and Hi-PoE standards, with a maximum output power consumption of 90W per port. Suitable for powering high-power devices.

Long Distance PoE

The transmission distance of a PoE port can be up to 250 m, meeting the requirement of wired transmission (bandwidth reduced to 10 Mbps).

PoE Watchdog

Adopts the innovative PoE Watchdog. It enables the switch to automatically detect port status and restart the failed ports to recover connection in case of IPC connection exception. This enables intelligent operation and maintenance management in its true sense and effectively reduces manual maintenance costs.

Port Isolation

Devices under different ports are prevented from communicating with each other, without need of VLAN being configured. Data is also protected from being leaked from the PoE ports and broadcast storms are isolated, making the network safe and easy to use.

- 24 × RJ-45 10/100 Mbps ports, 2 × RJ-45 10/100/1000 Mbps (combo) ports and 2 × SFP 1000 Mbps (combo) ports
- Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE, and IEEE802.3bt power supply standards
- PoE watchdog real-time monitors camera statues and automatically reboots faulty network cameras
- Up to 250 m transmission distance
- Supports VIP ports, prioritizing transmission for port1 to port8

Summary: Dahua Technology PoE S3226-24ET-375. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100), Basic switching RJ-45 Ethernet ports quantity: 24. Switching optical modules type: Gigabit Ethernet. MAC address table: 8000 entries, Switching capacity: 8.8 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3af, IEEE 802.3at, IEEE.... Power connector: AC-in jack. Power over Ethernet (PoE). Rack mounting | Vendor Homepage: https://transmission.dahuasecurity.com/en/product-

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

list/Business/Switches/PoESwitchForSecurity/S3226-24ET-375 | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 24 | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | Fast Ethernet (copper) ports quantity: 24 | Combo SFP ports quantity: 2 | Uplink ports quantity: 2 | Power connector: AC-in jack | Networking standards: IEEE 802.3/IEEE 802.3ab/IEEE 802.3af/IEEE 802.3at/IEEE 802.3bt/IEEE 802.3u/IEEE 802.3x/IEEE 802.3z | 10G support: No | Ethernet LAN data rates: 10,100 | Switching optical modules type: Gigabit Ethernet | Switching capacity: 8.8 | Forwarding rate: 6.55 | MAC address table: 8000 | Jumbo frames support: Yes | Jumbo frames: 15000 | Packet buffer memory: 4 | Rack mounting: Yes | Product colour: Black | Housing material: Metal | LED indicators: Yes | Power source: AC/PoE | Power supply included: Yes | Number of power supply units: 1 | AC input voltage: 100 - 240 | AC input frequency: 50/60 | Input current: 7 | Power consumption (max): 400 | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: Active PoE/PoE+/PoE++ (4PPoE) | Power over Ethernet (PoE) ports quantity: 24 | Power over Ethernet 4PPoE (PoE++) ports quantity: 2 | Total Power over Ethernet (PoE) budget: 375 | Operating temperature (T-T): -10 - 55 | Storage temperature (T-T): -40 - 75 | Operating relative humidity (H-H): 5 - 95 | Storage relative humidity (H-H): 5 - 95 | Width: 220 | Depth: 440 | Height: 44 | Weight: 2620 | Cables included: AC | Manual: Yes | Package type: Box | Package width: 342 | Package depth: 540 | Package height: 90 | Package weight: 3220 | Compliance certificates: CE | Unit Calculated Weight: 3.22 | Product Net Weight: 2.62 | Unit Calculated Volume: 0.01652 | Units per Shipping Box: 1 | Name: NET SWITCH 26PORT 24POE/S3226-24ET-375 DAHUA | Model name: S3226-24ET-375

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950