



Ruijie Networks RG-RAP62-OD wireless access point 2974 Mbit/s White Power over Ethernet (PoE)



Model: RG-RAP62-OD

Manufacturer: RUIJIE

EAN: 6976915001293

Product Code: 1182986

R5,398

Receiver sensitivity: 11b: -91dBm(1Mbps), -88dBm(5.5Mbps), -85dBm(11Mbps) 11a/g: -

89dBm(6Mbps), -80dBm(24Mbps), -76dBm(36Mbps) -71dBm(54Mbps) 11n: -83dBm(MCS0) -

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

65dBm(MCS7) - 83dBm(MCS8) -65dBm(MCS15) 11ac: 20MHz: -83dBm(MCS0), -57dBm(MCS9)
11ac: 40MHz: -79dBm(MCS0), -57dBm(MCS9) 11ac: 80MHz: -76dBm(MCS0), -51dBm(MCS9) 11ax:
20MHz: -85dBm(MCS0), -58dBm(MCS11) 11ax: 40MHz: -82dBm(MCS0), -54dBm(MCS11) 11ax:
80MHz: -79dBm(MCS0), -52dBm(MCS11) | Antenna gain level (max): 6.5 dBi | Networking standards:
IEEE 802.11b | Networking standards: IEEE 802.11a | Quantity per pack: 1 pc(s) | Networking
standards: IEEE 802.3af | Networking standards: IEEE 802.3at | Security algorithms: WPA2-AES |
MIMO: Yes | Security algorithms: WPA-TKIP | Reset button: Yes | Networking standards: IEEE 802.11g
| DC-in jack: No | Power consumption (typical): 16 W | Maximum data transfer rate (5 GHz): 2401
Mbit/s | Antenna type: Internal | Frequency band: 2.4 - 5 GHz | Networking standards: IEEE 802.11ax
| Security algorithms: WPA3-SAE | 5 GHz: Yes | Depth: 70 mm | International Protection (IP) code:
IP65 | LED indicators: System | Networking standards: IEEE 802.11ac | Placement: Pole, Wall |
Networking standards: IEEE 802.1x | Security algorithms: WPA-PSK | Ethernet LAN (RJ-45) ports: 1 |
Operating temperature (T-T): -30 - 65 °C | Antenna direction type: Omni-directional | Spread
spectrum method: OFDMA | Product colour: White | Storage temperature (T-T): -40 - 75 °C |
Networking standards: IEEE 802.11k | Security algorithms: OWE | Ethernet LAN data rates: 10 |
Networking standards: IEEE 802.11n | Storage relative humidity (H-H): 5 - 95% | Ethernet LAN data
rates: 1000 | Maximum data transfer rate: 2974 Mbit/s | Operating relative humidity (H-H): 5 - 95% |
Networking standards: IEEE 802.11r | Security algorithms: WPA2-PSK | 2.4 GHz: Yes | Ethernet LAN
data rates: 100 | Weight: 400 g | Power over Ethernet (PoE): Yes | Width: 200 mm | DHCP server: Yes
| Blacklist: Yes | Flash memory: 128 MB | VLAN support: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes |
Antenna included: Yes | Whitelist: Yes | Number of SSID supported: 8 | Wi-Fi roaming: Yes | Maximum
data transfer rate (2.4 GHz): 573 Mbit/s | DHCP snooping: Yes | Internal memory: 512 MB | MIMO
type: Multi User MIMO | Number of users: 512 user(s) | Height: 35 mm | IP Source Guard (IPSG): Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950