



TP-Link Omada ES208GP network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) DIN rail Black

Model: ES208GP

Manufacturer: TP-LINK

EAN: 1210002609708

Product Code: 1183104

R1,900

Height: 25.4 mm | LED indicators: Yes | Depth: 100.7 mm | Virtual LAN features: Port-based VLAN | Operating temperature (T-T): 0 - 40 °C | MAC address table: 8000 entries | Auto-negotiation: Yes | Port mirroring: Yes | Product colour: Black | 10G support: No | Virtual LAN features: Tagged VLAN | Networking standards: IEEE 802.3at | Web-based management: Yes | Loop protection: Yes | Switching capacity: 16 Gbit/s | Ethernet LAN data rates: 10,100,1000 Mbit/s | VLAN support: Yes | Quick start guide: Yes | Forwarding rate: 11.904 Mpps | Networking standards: IEEE 802.3bt |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Storage relative humidity (H-H): 5 - 90% | Multicast support: Yes | Packet buffer memory: 0.5 MB | Switch type: Managed | Cables included: Power | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Networking standards: IEEE 802.3af | Operating relative humidity (H-H): 10 - 90% | Basic switching RJ-45 Ethernet ports quantity: 8 | Total Power over Ethernet (PoE) budget: 64 W | Virtual LAN features: MTU VLAN | Flow control support: Yes | Power over Ethernet plus (PoE+) ports quantity: 8 | Number of VLANs: 4000 | Input current: 1.31 A | Auto MDI/MDI-X: Yes | Power source: DC | DHCP features: DHCP client | Power over Ethernet (PoE): Yes | Store-and-forward: Yes | Broadcast storm control: Yes | Jumbo frames support: Yes | Switch layer: L2 | Form factor: DIN rail | Link aggregation: Yes | Rack mounting: Yes | IGMP snooping: Yes | Width: 158 mm | DC input voltage: 53 V | Jumbo frames: 15000 | Transmission distance (max): 0.25 km | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | Cloud-managed: Yes | Power over Ethernet (PoE) type supported: PoE+

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950